

Strategic Review Highlights Heavy Rare Earths at Subron (formerly Cowalinya) (Updated)

Heavy Rare Earths Limited (“HRE” or “the Company”) is provides the attached updated announcement (‘Updated Announcement’) following the Company’s previous announcement dated 20 July 2026 and titled ‘Strategic Review Highlights Heavy Rare Earths at Subron (formerly Cowalinya)’.

The attached Updated Announcement includes the following additions:

- All Significant drill intervals >1000ppm TREO & associated REO distribution (MREO & HREO)
- All respective individual lanthanides assays to >1000ppm TREO intervals
- Complete drill collar table of >1000ppm TREO drill holes
- Inclusion of a compliance statement in relation to the Company’s mineral resource.

This announcement has been approved by the Board of HRE

For more information, please contact:

Jason Barnett
Managing Director
+61 03 8630 3321
info@hreltd.com.au

Alex Cowie
NWR Communications
+61 412 952 610
alexco@nwrcommunications.com.au

Strategic Review Highlights Heavy Rare Earths at Subron (formerly Cowalinya)

Highlights

- Initial findings of Strategic Review reveal high-grade mineralisation at Subron (formerly Cowalinya) with elevated grades of Total Rare Earths (TREO), specifically Heavy Rare Earths Oxides (HREO) and with a **peak HREO ratio of 70%**
- A combined ~12.9km of high grade HREO mineralised strike and 10 high grade domains have been identified along newly delineated Structural Corridors within the JORC 159Mt @ 870ppm TREO resource¹, with multiple others outside of the initial resource area
- Outstanding intercept at newly named Seawolf prospect of 8m @ 3057ppm TREO, **1344ppm HREO** average, with a **42% HREO ratio**, from 27m (AC360)
- Key drill database metrics to support higher grade TREO & HREO domains include:
 - 190 Significant Intercept (SI) drill intervals (>1000ppm TREO), for an average 1685ppm TREO, with **441ppm HREO** for a **25% HREO ratio**
 - 150 SI drill intervals (>300ppm HREO) for an average 1653ppm TREO, with **579ppm HREO** for a **38% HREO ratio**
- Cowalinya renamed Subron in view of the interpreted elongated geometry of the mineralised lodes, reminiscent of a '**submarine squa**dr**on**', and playing upon the demand of Rare Earths required for next-generation submarines.

Heavy Rare Earths Limited ("HRE" or "the Company") is pleased to announce its preliminary findings from the strategic review announced 30th June², with a focus on HREO, of its "**Subron Rare Earths Project**" (renamed from Cowalinya) in Western Australia. Managing Director and CEO, Jason Barnett, commented:

"The strategic review of Subron has been very rewarding, and the findings show it to be one of the highest HREO ratio residual clay deposits of its kind. This is supported by the drilling data showing 150 intersections grading above 300ppm HREO with an outstanding 441ppm HREO average grade and 38% HREO ratio. This has immense value and provides a clear point of difference from most rare earths projects."

The opportunity for HRE is that these exceptional high-grade HREO ratio zones may be amenable to concentrate and yield a far higher value proposition for processing. It's still early days and we have a lot of work to do on mineralogy, re-domaining the resource and metallurgical testwork, but with a significant amount of work done already, we have a head start and look forward to updating shareholders with the results."

¹ Refer to [ASX Announcement dated 3 October 2023](#)

² Refer to [ASX Announcement dated 30 June 2026](#)

Click [HERE](#) to can engage with the company and visit our investor hub

The Subron Rare Earths Project (formerly the Cowalinya project) is located in south-central Western Australia (Figure 1). Tenure is situated in an area of non-farming, unallocated crown land 110km NNE of the port of Esperance, and well located logistically, 350km south of the recently constructed Kalgoorlie Rare Earth Processing Facility.




Figure 1. The location of HRE's Subron (formerly Cowalinya) REE Project is close to Esperance port and the Kalgoorlie Rare Earth Processing Facility.

Of strategic interest to the refreshed HRE board are areas of higher grade REE's that are enriched in the HREOs (Eu + Gd + Tb + Dy + Ho + Er + Tm + Yb + Lu + Y). A review on this basis of the existing drilling database comprising 547 aircore (AC) holes completed by the Company (and previous explorers), successfully identified hundreds of significant intersections that support the presence of such higher-grade TREO and HREO domains.

For example:

- Applying a >1000ppm TREO cut-off results in:
 - 190 Significant Intercept drill intervals, including:
 - 583 individual 1m intervals grading > 1000ppm TREO
 - For an average 1685ppm TREO, with 441ppm HREO representing a 25% HREO ratio

- Applying a >300ppm HREO cut-off results in:
 - 150 Significant Intercept drill intervals; including:
 - 454 individual 1m intervals grading > 300ppm HREO
 - for an average 1653ppm TREO, with 579ppm HREO representing a 38% HREO ratio

The distribution of the rare earth oxides (REO) within the Subron >300ppm HREO dataset is presented in the pie chart below. The discovery of this higher grade, higher value composition of rare earths presents a new value proposition at Subron given the demand, and strategic value of the heavy rare earth element oxides **Yttrium oxide** (Y_2O_3), **Terbium oxide** (Tb_4O_7) and **Dysprosium oxide** (Dy_2O_3).




Figure 2. Rare earth oxide distribution with Subron's >300ppm HREO drilling assays

Subron Strategic Review Background

The Company engaged Rare Earths & Critical Minerals consultant Claudio Sheriff to undertake the Strategic Review of Subron. Mr Sheriff has been involved in several Rare Earths discoveries, including Voltaic's Strategic Resources' (ASX:VSR) '**Neo MREO-Ga**' discovery in the Gascoyne; Asra Minerals's (ASX:ASR) '**Yttria-REO-Sc**' Residual Clay deposit discovery; and Northern Minerals' (ASX:NTU) '**Wolverine**' HREE deposit.

Mr Sheriff commented:

“A total of 547 AC drill holes have been reviewed with a focus on HREO distribution, constrained by regional magnetics and structural interpretation. The preliminary findings of the focus on the distribution of the HREOs is awakening a re-rate at Subron as understanding of its composition evolves, given the tenor of HREO ratio and vast incidence of significant intercepts above the existing resource grade.

Residual clay occurrences aren’t rare, however a cluster of HREO domains in a Sea of regional prospectivity, emerging at Subron, are remarkable.

*The name ‘Subron’, short for **Submarine Squadron**, refers to the interpreted submarine-like geometry of the HREO-rich mineralisation and symbolically reflects it’s potential as a source of heavy rare earths for the AUKUS submarine program.”*

High Grade HREO Interpreted Mineralised Domains

10 HREO high grade domains have been constrained by drill intercepts, delineated by underlying magnetics and interpreted structural trends. Regional structural corridors constraining and controlling mineralisation have been named after historically submarine-prominent seas (Barents, Bering, Bismarck).

These domains represent a **combined ~12.9km of high grade HREO mineralised strike** and bolsters Subron’s potential for a meaningful resource of higher-grade material. These initial observations will be followed up by re-domaining the current JORC mineral resource at Subron.

The Seawolf Prospect is a priority target, it has the highest-grade intersections at Subron recording **8m @ 3057ppm TREO, 1344ppm HREO average, with a 42% HREO ratio**. Additional drilling at Seawolf and other prospects will be required to better define the high-grade mineralisation and convert Inferred resources to Indicated.

Table 1. Interpreted high grade domains and significant intercepts at Subron

Structural Corridor	HG Domain	Strike (Km)	Width (Km)	Significant Intercept	HREO Ratio
BERING	Nordenfelt	1.7	0.15	11m @ 4606ppm TREO (from 24m AC225) inc 1365ppm HREO	31%
				4m @ 1936ppm TREO (from 27m AC275) inc 1065ppm HREO	55%
	Oberon	1.5	0.15	10m @ 1782ppm TREO (from 14m AC28) inc 343ppm HREO	36%
				6m @ 1434ppm TREO (from 24m AC16) inc 454ppm HREO	31%
	Narval	1.0	0.10	4m @ 2487ppm TREO (from 31m AC279) inc 975ppm HREO	39%
	Tunny	0.5	0.20	2m @ 2753ppm TREO (from 26m AC343) inc 1019ppm HREO	37%
BISMARCK	Virginia	2.5	0.20	2m @ 3068ppm TREO (from 32m AC201) inc 1002ppm HREO	33%
				4m @ 2593ppm TREO (from 20m AC200) inc 1453ppm HREO	57%
				4m @ 2360ppm TREO (from 30m AC356) inc 1237ppm HREO	52%
	Seawolf	1.5	0.20	2m @ 3795ppm TREO (from 24m AC361) inc 1918ppm HREO	51%
				8m @ 3057ppm TREO (from 27m AC360) inc 1344ppm HREO	42%
	Hunley	1.5	0.15	2m @ 3196ppm TREO (from 34m AC326) inc 1236ppm HREO	39%
				2m @ 3611ppm TREO (from 36m AC363) inc 1751ppm HREO	48%
	Blume	0.9	0.10	3m @ 2246ppm TREO (from 38m AC321) inc 1481ppm HREO	66%
REGIONAL	Garrett	1.0	0.15	2m @ 4087ppm TREO (from 18m AC412) inc 1210ppm HREO	30%
				6m @ 2383ppm TREO (from 16m AC440) inc 911ppm HREO	39%




Figure 3. Subron's high-grade domains are elongated and strike parallel with regional structures.

Next Steps

We are highly encouraged by the findings from this strategic review which has identified high grade zones of rare earth mineralisation with HREO ratios > 38%. The high number of drill intersections and the widely spaced drilling provide an exciting opportunity to add a high-grade, high-HREO, material resource within the broader mineralised region.

We look forward to further updating the market on additional findings as we complete the strategic review of Subron, with further assessment, results, and recommendations expected in the coming weeks.

At this early stage we expect future news flow to address regional opportunities to build additional scale and zones of most likely secondary mineralisation to be selected for mineralogy characterisation work.

The company aims to confirm the availability of AC drilling variability samples, which would avoid re-drilling for material of interest and enables fast-tracking of this priority metallurgical testwork.

Additional work will include a maiden high-grade, high-HREO-ratio mineral resource estimation, metallurgical testwork aimed at specific layers within the geology to simplify the processing flowsheet, and potentially resource infill drilling to convert Inferred resources to Indicated and extend high grade domains.




Figure 4. HRE's high grade prospects, regional targets and conceptual targets at Subron.

— ENDS —

This announcement has been approved by the Board of HRE

For more information, please contact:

Jason Barnett
Managing Director
+61 03 8630 3321
info@hreltd.com.au

Alex Cowie
NWR Communications
+61 412 952 610
alexc@nwrcommunications.com.au

About Heavy Rare Earths Limited

Heavy Rare Earths Limited (ASX:HRE) is an Australian uranium and critical minerals exploration and development company.

Competent Person's Statement

The Exploration Results contained in this announcement were compiled by Mr Claudio Sheriff. Mr Sheriff is a member of the Australasian Institute of Mining and Metallurgy. He is a consultant to Heavy Rare Earths Limited. Mr Sheriff has more than 20 years' experience in mineral exploration and has sufficient experience relevant to the style of mineralisation and type of deposit under consideration to qualify as a Competent Person as defined in the 2012 JORC Code. Mr Sheriff consents to the inclusion in this announcement of the matters based on the Exploration Results in the form and context in which they appear.

Compliance Statement

The information in this report that relates to Mineral Resources is extracted from the ASX announcement entitled "FIVE-FOLD INCREASE IN MINERAL RESOURCES TO 159 Mt @ 870 ppm TOTAL RARE EARTH OXIDES AT COWALINYA PROJECT IN WESTERN AUSTRALIA" dated 3 October 2023, which is available to view on the ASX website. The Company confirms that it is not aware of any new information or data that materially affects the information included in the original market announcement. The Company confirms that the form and context in which the Competent Person's findings are presented have not been materially modified from the original market announcement. The Company confirms that all material assumptions and technical parameters underpinning the estimates in the relevant market announcement continue to apply and have not materially changed.

Forward Looking Statement

This announcement includes "forward-looking statements" as that term within the meaning of securities laws of applicable jurisdictions. Forward-looking statements involve known and unknown risks, uncertainties and other factors that are in some cases beyond HRE's control. These forward-looking statements include, but are not limited to, all statements other than statements of historical facts contained in this presentation, including, without limitation, those regarding HRE's future expectations. Readers can identify forward-looking statements by terminology such as "aim," "anticipate," "assume," "believe," "continue," "could," "estimate," "expect," "forecast," "intend," "may," "plan," "potential," "predict," "project," "risk," "should," "will" or "would" and other similar expressions. Risks, uncertainties and other factors may cause HRE's actual results, performance, production or achievements to differ materially from those expressed or implied by the forward-looking statements (and from past results, performance or achievements). Readers are cautioned not to place undue reliance on forward-looking statements. Although HRE believes that its expectations reflected in these forward-looking statements are reasonable, such statements involve risks and uncertainties and no assurance can be given that actual results will be consistent with these forward-looking statements.

Table 2. Subron Collar Table for air core holes for which high grade HREO assays are reported

HOLE ID	NORTHING	EASTING	DEPTH	DIP	RL
AC16	6358600	432600	32	90	253.2
AC28	6359000	432100	39	90	256.8
AC200	6358201	429002	44	90	254.4
AC201	6358191	428802	47	90	256.7
AC225	6359305	430000	36	90	259.4
AC275	6359002	430399	38	90	259.7
AC279	6359017	429598	40	90	258.6
AC321	6358196	426808	42	90	252.4
AC326	6358198	427799	49	90	254.4
AC343	6357809	432402	35	90	255.1
AC356	6357797	429798	59	90	256.4
AC360	6357800	428997	46	90	253.7
AC361	6357799	428801	27	90	257.1
AC363	6357801	428403	46	90	260.4
AC412	6356601	431203	41	90	258.1
AC440	6354200	433800	40	90	254.6

Annexure A – Table of results >1,000ppm TREO - Summary of REO distribution

(Highlighted – MREO >500ppm and HREO>500ppm)

Hole ID	From (m)	To (m)	Interval (m)	MREO ppm	MREO/TREO %	HREO ppm	HREO/TREO %	TREO ppm
AC1	34	36	2	354	30%	421	36%	1166
AC2	16	18	2	476	34%	336	24%	1402
AC2	18	20	2	370	31%	227	19%	1190
AC2	20	22	2	383	28%	255	19%	1368
AC2	22	24	2	483	28%	342	20%	1730
AC2	26	28	2	364	29%	180	14%	1251
AC2	28	30	2	393	33%	157	13%	1193
AC4	26	28	2	430	36%	313	26%	1194
AC4	30	32	2	342	31%	208	19%	1087
AC4	34	35	1	394	31%	232	18%	1292
AC4	35	36	1	278	26%	178	17%	1066
AC5	32	34	2	363	36%	142	14%	1014
AC5	34	36	2	630	40%	211	13%	1582
AC6	26	28	2	271	25%	125	12%	1068
AC6	28	30	2	314	27%	122	10%	1175
AC6	30	32	2	284	27%	120	11%	1056
AC8	24	26	2	523	37%	359	25%	1414
AC8	26	28	2	768	36%	839	39%	2132
AC8	28	29	1	323	29%	469	42%	1107
AC9	28	29	1	309	28%	527	49%	1085
AC12	18	20	2	703	30%	344	15%	2313
AC12	20	22	2	231	19%	161	13%	1232
AC13	20	21	1	217	21%	131	13%	1038
AC16	22	24	2	329	32%	237	23%	1040
AC16	24	26	2	539	35%	463	30%	1533
AC16	26	28	2	587	35%	582	35%	1679
AC16	28	30	2	340	31%	317	29%	1089
AC17	28	30	2	374	28%	229	17%	1332
AC17	30	32	2	315	30%	456	44%	1042
AC17	32	34	2	342	27%	453	36%	1266
AC17	34	36	2	301	25%	565	48%	1188
AC18	16	18	2	835	49%	374	22%	1711
AC21	22	24	2	446	35%	423	33%	1292
AC21	24	26	2	324	32%	372	37%	1009
AC21	26	27	1	567	36%	532	34%	1561
AC21	27	28	1	343	32%	406	38%	1082
AC27	30	32	2	285	27%	411	39%	1043
AC27	32	34	2	407	30%	344	26%	1342
AC28	14	16	2	471	36%	492	37%	1315
AC28	16	18	2	582	40%	489	33%	1468

Hole ID	From (m)	To (m)	Interval (m)	MREO ppm	MREO/TREO %	HREO ppm	HREO/TREO %	TREO ppm
AC28	18	20	2	523	36%	498	35%	1436
AC28	20	22	2	1287	46%	964	34%	2807
AC28	22	24	2	776	41%	771	41%	1884
AC28	34	36	2	366	35%	252	24%	1045
AC28	38	39	1	349	32%	305	28%	1080
AC29	20	22	2	1355	37%	788	21%	3677
AC29	22	24	2	438	24%	280	15%	1861
AC29	24	26	2	425	26%	319	20%	1614
AC29	26	28	2	1024	36%	711	25%	2883
AC29	30	32	2	552	39%	441	31%	1426
AC29	32	34	2	812	36%	783	35%	2252
AC30	30	32	2	332	27%	126	10%	1241
AC33	16	18	2	489	30%	45	3%	1606
AC33	26	28	2	466	33%	412	29%	1431
AC35	18	20	2	1028	43%	734	31%	2383
AC35	24	26	2	305	26%	211	18%	1181
AC35	28	30	2	299	27%	255	23%	1106
AC36	28	30	2	246	24%	508	49%	1040
AC37	20	21	1	360	27%	461	34%	1350
AC41	14	16	2	548	42%	389	30%	1308
AC41	22	24	2	317	32%	305	30%	1001
AC42	12	14	2	219	21%	25	2%	1038
AC58	26	28	2	410	27%	205	14%	1506
AC60	26	27	1	352	32%	400	37%	1092
AC70	20	22	2	300	30%	47	5%	1017
AC81	24	26	2	1412	46%	843	27%	3095
AC81	26	28	2	1022	34%	1117	38%	2970
AC89	16	18	2	583	45%	53	4%	1299
AC89	26	28	2	739	35%	708	33%	2133
AC89	28	30	2	454	35%	392	30%	1316
AC89	30	32	2	319	31%	286	27%	1040
AC90	32	34	2	531	40%	498	37%	1332
AC90	34	36	2	461	42%	406	37%	1092
AC101	22	24	2	412	34%	417	35%	1194
AC101	24	25	1	416	38%	305	28%	1085
AC104	26	28	2	321	28%	488	43%	1133
AC104	28	30	2	352	31%	350	31%	1143
AC110	22	24	2	610	35%	481	28%	1727
AC110	28	29	1	356	28%	398	31%	1287
AC111	22	24	2	362	34%	246	23%	1068
AC112	21	23	2	582	39%	556	38%	1482
AC115	26	28	2	706	37%	403	21%	1922

Hole ID	From (m)	To (m)	Interval (m)	MREO ppm	MREO/TREO %	HREO ppm	HREO/TREO %	TREO ppm
AC115	28	29	1	505	31%	557	34%	1639
AC119	18	20	2	316	28%	59	5%	1148
AC122	18	20	2	714	32%	350	16%	2255
AC123	15	17	2	308	25%	61	5%	1230
AC129	21	23	2	397	21%	111	6%	1930
AC130	20	22	2	242	20%	107	9%	1212
AC130	32	34	2	296	29%	197	19%	1013
AC131	23	25	2	242	24%	17	2%	1000
AC134	14	16	2	468	29%	88	5%	1602
AC136	18	20	2	471	32%	484	33%	1457
AC137	17	19	2	416	41%	277	27%	1024
AC137	25	27	2	307	27%	638	56%	1132
AC142	16	18	2	447	29%	41	3%	1526
AC175	12	14	2	304	24%	133	10%	1286
AC179	16	18	2	691	32%	695	32%	2176
AC179	18	20	2	332	28%	409	35%	1177
AC181	17	19	2	518	40%	278	22%	1284
AC181	23	25	2	292	28%	165	16%	1045
AC184	22	24	2	332	31%	98	9%	1077
AC192	31	32	1	491	30%	357	22%	1618
AC194	22	24	2	476	43%	415	38%	1096
AC196	29	31	2	452	31%	681	47%	1441
AC198	41	43	2	556	39%	421	29%	1437
AC200	20	22	2	1000	35%	1381	48%	2869
AC200	22	24	2	664	29%	1525	66%	2317
AC201	32	34	2	1334	43%	1002	33%	3068
AC212	24	26	2	973	38%	554	22%	2563
AC212	26	28	2	604	40%	343	23%	1517
AC213	21	23	2	535	43%	354	28%	1246
AC213	23	25	2	394	38%	331	32%	1031
AC221	17	19	2	1758	31%	994	17%	5688
AC221	19	21	2	825	29%	581	20%	2843
AC223	17	19	2	525	40%	276	21%	1309
AC223	19	21	2	717	40%	475	26%	1804
AC223	23	25	2	483	28%	425	25%	1731
AC223	25	27	2	446	22%	626	30%	2062
AC225	16	18	2	491	40%	169	14%	1238
AC225	18	20	2	457	32%	309	21%	1449
AC225	20	22	2	330	26%	243	19%	1273
AC225	22	24	2	215	21%	111	11%	1017
AC225	24	26	2	2965	48%	1437	23%	6211
AC225	26	28	2	3731	52%	1814	25%	7222

Hole ID	From (m)	To (m)	Interval (m)	MREO ppm	MREO/TREO %	HREO ppm	HREO/TREO %	TREO ppm
AC225	28	30	2	1813	44%	1486	36%	4110
AC225	30	32	2	1557	39%	1467	37%	3983
AC225	32	34	2	912	38%	811	34%	2415
AC225	34	35	1	864	31%	989	36%	2782
AC226	26	28	2	531	34%	439	28%	1584
AC226	28	30	2	1060	38%	926	33%	2793
AC226	30	32	2	318	32%	257	25%	1009
AC226	46	48	2	364	28%	790	61%	1292
AC232	18	20	2	385	35%	83	8%	1086
AC232	20	21	1	423	36%	112	9%	1192
AC232	21	23	2	556	40%	174	13%	1376
AC235	25	27	2	288	28%	402	38%	1045
AC244	22	24	2	763	48%	527	33%	1584
AC244	26	27	1	304	28%	149	14%	1099
AC245	26	27	1	358	27%	77	6%	1347
AC246	18	20	2	472	37%	321	25%	1291
AC263	20	22	2	1187	45%	920	35%	2631
AC263	22	24	2	330	32%	319	31%	1027
AC265	32	34	2	347	28%	548	44%	1256
AC265	38	40	2	272	22%	168	14%	1234
AC268	26	28	2	904	36%	844	34%	2513
AC269	12	14	2	483	31%	179	11%	1579
AC269	14	16	2	459	27%	127	7%	1713
AC269	18	20	2	340	24%	92	6%	1446
AC269	22	24	2	380	32%	108	9%	1192
AC274	16	18	2	379	25%	297	20%	1506
AC274	18	20	2	401	35%	362	31%	1156
AC274	20	22	2	917	43%	771	36%	2117
AC274	22	24	2	622	35%	604	34%	1798
AC274	24	26	2	414	34%	440	36%	1217
AC274	26	28	2	370	34%	346	32%	1076
AC274	32	34	2	394	27%	396	28%	1437
AC275	19	21	2	1043	30%	187	5%	3492
AC275	23	25	2	227	22%	382	37%	1036
AC275	25	27	2	302	23%	448	34%	1325
AC275	27	29	2	563	29%	1170	61%	1932
AC275	29	31	2	602	31%	959	49%	1940
AC275	31	33	2	274	27%	598	59%	1005
AC279	31	33	2	991	41%	853	35%	2421
AC279	33	35	2	869	34%	1098	43%	2552
AC279	35	37	2	425	34%	432	35%	1250
AC280	20	22	2	602	34%	617	35%	1788
AC281	22	24	2	443	31%	247	17%	1412

Hole ID	From (m)	To (m)	Interval (m)	MREO ppm	MREO/TREO %	HREO ppm	HREO/TREO %	TREO ppm
AC281	26	28	2	324	31%	132	13%	1058
AC282	21	23	2	443	41%	198	18%	1087
AC286	13	15	2	200	16%	77	6%	1256
AC287	20	22	2	311	24%	74	6%	1300
AC287	24	26	2	557	34%	207	13%	1621
AC289	17	19	2	383	35%	253	23%	1084
AC289	25	27	2	373	30%	243	19%	1254
AC292	21	23	2	306	27%	109	10%	1146
AC292	27	29	2	533	36%	157	11%	1494
AC295	19	21	2	514	36%	227	16%	1421
AC301	22	24	2	356	31%	96	8%	1156
AC301	26	28	2	358	36%	131	13%	1001
AC302	26	28	2	1549	45%	550	16%	3455
AC302	28	30	2	484	40%	246	20%	1207
AC305	23	25	2	441	35%	447	35%	1270
AC306	19	21	2	688	42%	466	28%	1637
AC309	31	33	2	330	29%	298	26%	1133
AC309	35	37	2	385	33%	393	33%	1174
AC311	14	16	2	147	14%	20	2%	1028
AC312	38	40	2	266	25%	324	31%	1051
AC312	40	42	2	262	23%	535	46%	1159
AC321	38	40	2	590	27%	1499	68%	2200
AC321	40	41	1	660	28%	1447	62%	2337
AC322	25	27	2	479	36%	327	24%	1339
AC322	27	29	2	376	36%	394	38%	1048
AC324	24	25	1	1332	44%	962	32%	3046
AC326	34	36	2	1169	37%	1236	39%	3196
AC328	30	32	2	546	36%	647	42%	1534
AC343	24	26	2	433	37%	210	18%	1155
AC343	26	28	2	1079	39%	1019	37%	2753
AC344	26	28	2	582	24%	346	14%	2417
AC344	28	30	2	431	27%	149	9%	1600
AC344	32	34	2	327	26%	343	27%	1270
AC350	19	21	2	397	29%	148	11%	1367
AC354	19	21	2	623	33%	477	25%	1914
AC354	27	29	2	550	34%	518	32%	1611
AC356	30	32	2	540	34%	787	49%	1589
AC356	32	34	2	1080	34%	1687	54%	3131
AC359	16	18	2	2575	53%	253	5%	4839
AC359	22	24	2	659	42%	118	8%	1569
AC360	27	29	2	1106	40%	671	24%	2756
AC360	29	31	2	1550	43%	1393	39%	3608

Hole ID	From (m)	To (m)	Interval (m)	MREO ppm	MREO/TREO %	HREO ppm	HREO/TREO %	TREO ppm
AC360	31	33	2	1117	28%	2552	63%	4042
AC360	33	35	2	692	38%	759	42%	1820
AC361	22	24	2	335	28%	399	34%	1183
AC361	24	26	2	1106	29%	1918	51%	3795
AC363	34	36	2	440	35%	387	31%	1263
AC363	36	38	2	1203	33%	1751	48%	3611
AC366	31	33	2	253	25%	82	8%	1010
AC374	32	34	2	344	25%	542	39%	1376
AC382	17	19	2	853	45%	429	23%	1889
AC387	30	32	2	462	35%	386	29%	1312
AC387	32	34	2	511	35%	484	33%	1471
AC387	36	38	2	549	31%	468	26%	1784
AC388	21	23	2	506	27%	553	30%	1862
AC389	22	24	2	354	34%	372	36%	1038
AC391	28	30	2	1148	41%	909	32%	2807
AC396	20	22	2	928	37%	554	22%	2526
AC406	16	18	2	223	22%	13	1%	1002
AC409	21	23	2	265	24%	126	11%	1111
AC411	23	25	2	607	37%	578	35%	1638
AC412	18	20	2	1870	46%	1210	30%	4087
AC412	22	24	2	322	27%	296	25%	1204
AC413	21	23	2	282	27%	464	45%	1036
AC415	13	15	2	632	36%	594	34%	1743
AC415	15	17	2	570	34%	600	36%	1671
AC417	25	27	2	441	39%	380	34%	1133
AC417	27	29	2	432	31%	606	44%	1375
AC418	21	23	2	525	29%	228	12%	1831
AC418	23	25	2	627	27%	629	28%	2282
AC419	34	36	2	305	28%	479	45%	1076
AC424	9	11	2	574	56%	84	8%	1030
AC424	11	13	2	2128	66%	325	10%	3209
AC424	21	23	2	805	41%	697	35%	1968
AC424	23	25	2	655	33%	639	32%	1984
AC429	29	31	2	307	27%	336	30%	1129
AC430	19	21	2	577	39%	505	34%	1465
AC431	34	36	2	302	26%	339	29%	1175
AC433	18	20	2	255	25%	174	17%	1039
AC433	20	22	2	280	27%	211	21%	1018
AC433	24	26	2	389	33%	364	30%	1196
AC440	16	18	2	309	29%	445	42%	1071
AC440	18	20	2	1022	38%	1012	38%	2695
AC440	20	22	2	1328	39%	1277	38%	3385

Hole ID	From (m)	To (m)	Interval (m)	MREO ppm	MREO/TREO %	HREO ppm	HREO/TREO %	TREO ppm
AC441	10	12	2	460	27%	156	9%	1677
AC445	17	19	2	1224	47%	663	25%	2632
AC446	22	24	2	330	24%	101	7%	1376
AC446	24	26	2	524	22%	141	6%	2409
AC446	26	28	2	332	24%	146	11%	1371
AC446	28	30	2	302	25%	111	9%	1228
AC447	21	23	2	435	37%	230	19%	1189
AC452	21	23	2	426	32%	157	12%	1332
AC452	23	25	2	417	36%	161	14%	1161
AC453	24	26	2	199	16%	808	66%	1227
AC455	16	18	2	476	39%	125	10%	1234
AC458	37	39	2	367	29%	108	8%	1281
AC458	39	41	2	345	31%	113	10%	1106
AC467	23	25	2	511	41%	117	9%	1239
AC467	27	29	2	801	44%	212	12%	1811
AC467	29	31	2	798	43%	248	13%	1866
AC467	33	35	2	426	39%	185	17%	1105
AC467	37	39	2	336	33%	192	19%	1032
AC468	15	17	2	512	46%	92	8%	1115
AC468	25	27	2	384	34%	101	9%	1122
AC468	27	29	2	706	42%	291	17%	1693
AC468	29	31	2	455	35%	362	28%	1290
AC468	31	33	2	745	28%	325	12%	2631
AC469	31	33	2	311	30%	117	11%	1024
AC470	22	24	2	478	38%	247	19%	1269
AC471	18	20	2	548	43%	238	19%	1276
AC471	20	22	2	1029	41%	540	22%	2491
AC471	22	24	2	491	39%	280	22%	1263
AC472	21	23	2	325	23%	791	55%	1431
AC473	9	11	2	695	30%	294	13%	2319
AC473	11	13	2	344	32%	131	12%	1061
AC473	13	14	1	307	30%	106	10%	1015
AC487	18	20	2	502	27%	210	11%	1850
AC487	20	22	2	1366	26%	889	17%	5193
AC487	22	24	2	298	26%	148	13%	1126
AC492	15	17	2	279	21%	108	8%	1319
AC494	17	19	2	725	35%	219	11%	2068
AC494	19	21	2	555	38%	186	13%	1479
AC497	19	21	2	598	38%	489	31%	1564
AC509	26	28	2	448	37%	209	17%	1200
AC511	20	22	2	400	24%	280	17%	1695
AC511	22	24	2	358	28%	445	34%	1298
AC518	21	23	2	329	20%	45	3%	1630

Hole ID	From (m)	To (m)	Interval (m)	MREO ppm	MREO/TREO %	HREO ppm	HREO/TREO %	TREO ppm
AC520	31	33	2	1079	31%	934	27%	3449
AC532	36	38	2	629	39%	275	17%	1612
AC532	38	40	2	554	36%	425	28%	1525
AC540	25	27	2	665	32%	664	32%	2071
AC540	27	29	2	416	31%	317	23%	1358
AC544	31	33	2	345	25%	196	14%	1351
AC544	33	35	2	367	25%	171	12%	1454
AC544	35	37	2	317	31%	224	22%	1031

Annexure B – Table of Drill Collars for all >1000ppm TREO intercepts

HOLE ID	NORTHING	EASTING	DEPTH	DIP	RL
AC1	6358200	433200	39	90	270.2
AC2	6358200	433100	34	90	268.8
AC4	6358200	432600	36	90	280.9
AC5	6358200	432500	36	90	279.2
AC6	6358200	432400	32	90	277.0
AC8	6358200	432200	29	90	272.8
AC9	6358200	432100	30	90	270.6
AC12	6358600	433000	29	90	266.1
AC13	6358600	432900	21	90	265.4
AC16	6358600	432600	32	90	262.0
AC17	6358600	432500	39	90	260.5
AC18	6358600	432400	26	90	260.5
AC21	6358600	432100	28	90	262.0
AC27	6359000	432200	39	90	266.5
AC28	6359000	432100	39	90	266.0
AC29	6359000	432000	39	90	265.0
AC30	6359000	431900	39	90	264.0
AC33	6359000	431600	31	90	263.3
AC35	6359000	431400	33	90	259.4
AC36	6359020	431300	31	90	258.0
AC37	6359040	431200	21	90	257.5
AC41	6359365	430900	30	90	263.1
AC42	6359380	431000	22	90	263.1
AC58	6360600	430200	30	90	259.2
AC60	6360750	428150	27	90	261.4
AC70	6361000	427950	28	90	258.1
AC81	6361000	427300	36	90	258.0
AC89	6361250	427500	44	90	258.1
AC90	6361250	427400	36	90	258.9
AC101	6361500	427250	25	90	255.2
AC104	6361755	427245	39	90	257.0
AC110	6358001	432626	29	90	262.6
AC111	6357803	432597	31	90	262.8
AC112	6357601	432581	30	90	263.4
AC115	6357003	432618	30	90	260.8
AC119	6356202	432620	26	90	258.4
AC122	6357004	434595	22	90	271.9
AC123	6356803	434584	19	90	269.5
AC129	6355602	434612	34	90	262.6

HOLE ID	NORTHING	EASTING	DEPTH	DIP	RL
AC130	6355405	434624	45	90	261.9
AC131	6355202	434614	28	90	261.0
AC134	6354605	434565	19	90	256.0
AC136	6354202	434630	22	90	255.9
AC137	6354996	433799	30	90	256.4
AC142	6354999	435001	26	90	259.9
AC175	6356590	431801	45	90	258.7
AC179	6358206	433800	45	90	267.6
AC181	6358204	433399	27	90	265.5
AC184	6358201	432805	25	90	261.6
AC192	6358206	430603	33	90	259.2
AC194	6358205	430198	50	90	257.7
AC196	6358202	429801	38	90	257.2
AC198	6358205	429402	46	90	259.2
AC200	6358201	429002	44	90	254.4
AC201	6358191	428802	47	90	256.7
AC212	6359813	430201	37	90	263.3
AC213	6359785	430000	39	90	261.5
AC221	6358596	428000	47	90	254.4
AC223	6359308	430398	29	90	258.1
AC225	6359305	430000	36	90	259.4
AC226	6359329	429799	55	90	260.1
AC232	6359395	427600	28	90	258.0
AC235	6359819	428196	27	90	260.4
AC244	6358993	434197	28	90	268.4
AC245	6359019	434404	28	90	270.6
AC246	6359023	434001	26	90	268.0
AC263	6359812	429196	24	90	263.2
AC265	6359463	429000	41	90	264.2
AC268	6359402	427798	37	90	259.9
AC269	6359394	427399	23	90	259.6
AC274	6358997	430601	41	90	260.1
AC275	6359002	430399	38	90	259.7
AC279	6359017	429598	40	90	258.6
AC280	6359006	429399	39	90	257.9
AC281	6359014	429198	34	90	259.5
AC282	6359018	428996	28	90	263.7
AC286	6358990	428198	28	90	254.6
AC287	6359001	427997	44	90	254.2
AC289	6358985	427599	36	90	256.3
AC292	6359002	427204	41	90	255.8
AC295	6358598	426999	31	90	255.8

HOLE ID	NORTHING	EASTING	DEPTH	DIP	RL
AC301	6358580	429204	33	90	255.5
AC302	6358580	429402	33	90	255.5
AC305	6358666	430000	40	90	255.1
AC306	6358634	430204	30	90	259.1
AC309	6358579	430808	42	90	259.5
AC311	6358602	431208	31	90	260.9
AC312	6358599	431399	55	90	262.9
AC321	6358196	426808	42	90	255.2
AC322	6358197	427000	42	90	254.6
AC324	6358196	427402	26	90	255.4
AC326	6358198	427799	49	90	254.4
AC328	6358198	428201	37	90	258.4
AC343	6357809	432402	35	90	264.4
AC344	6357813	432197	35	90	263.3
AC350	6357773	430997	28	90	259.2
AC354	6357786	430201	30	90	258.7
AC356	6357797	429798	59	90	256.4
AC359	6357798	429199	51	90	255.7
AC360	6357800	428997	46	90	253.7
AC361	6357799	428801	27	90	257.1
AC363	6357801	428403	46	90	260.4
AC366	6357798	427801	34	90	255.1
AC374	6357380	433602	42	90	265.1
AC382	6357401	431799	30	90	262.0
AC387	6357360	430803	46	90	258.7
AC388	6357415	430602	30	90	258.0
AC389	6357399	430403	31	90	257.1
AC391	6357399	429999	37	90	257.2
AC396	6357012	433198	25	90	261.5
AC406	6357005	431001	21	90	259.7
AC409	6356998	430398	26	90	257.1
AC411	6356603	431401	36	90	258.4
AC412	6356601	431203	41	90	258.1
AC413	6356600	430996	28	90	257.1
AC415	6356604	430605	28	90	252.5
AC417	6356600	430199	30	90	255.6
AC418	6356597	430006	27	90	256.2
AC419	6356188	432792	38	90	259.7
AC424	6356201	431602	26	90	256.6
AC429	6356198	430599	32	90	256.9
AC430	6356194	430401	30	90	256.7
AC431	6356199	430204	37	90	255.4

HOLE ID	NORTHING	EASTING	DEPTH	DIP	RL
AC433	6354597	434002	33	90	254.1
AC440	6354200	433800	40	90	254.6
AC441	6354202	433597	23	90	255.0
AC445	6362090	425792	21	90	258.4
AC446	6362103	424987	46	90	260.2
AC447	6362109	424589	28	90	NA
AC452	6362139	422593	40	90	NA
AC453	6362144	422192	28	90	NA
AC455	6362612	421398	31	90	NA
AC458	6363814	421420	49	90	NA
AC467	6367069	418275	51	90	NA
AC468	6367071	417472	47	90	NA
AC469	6367076	417074	49	90	NA
AC470	6367069	416672	44	90	NA
AC471	6367086	416273	27	90	NA
AC472	6367075	415874	31	90	NA
AC473	6367085	415466	15	90	NA
AC487	6361245	425397	29	90	262.7
AC492	6362095	425393	26	90	262.6
AC494	6360746	426000	35	90	263.7
AC497	6360749	427199	30	90	261.2
AC509	6356205	435200	51	90	266.1
AC511	6356184	435601	28	90	266.4
AC518	6355384	435600	28	90	263.6
AC520	6355391	436001	40	90	268.9
AC532	6364711	429572	47	90	NA
AC540	6354201	435998	31	90	258.8
AC544	6358203	432610	40	90	261.2

Annexure C – Table of lanthanides assays for all >1,000ppm TREO intervals (Highlighted - Pr>100 ppm Nd>400 ppm Tb>10ppm Dy>60 ppm Y>300ppm)

Hole ID	From (m)	To (m)	Interval (m)	La2O3 ppm	CeO2 ppm	Pr6O11 ppm	Nd2O3 ppm	Sm2O3 ppm	Eu2O3 ppm	Gd2O3 ppm	Tb4O7 ppm	Dy2O3 ppm	Ho2O3 ppm	Er2O3 ppm	Tm2O3 ppm	Yb2O3 ppm	Lu2O3 ppm	Y2O3 ppm
AC1	34	36	2	127.8	314.5	42.3	213.5	47.1	9.3	47.4	7.2	43.5	8.9	24.9	3.5	19.5	2.6	254
AC2	16	18	2	267.4	359.9	75.9	304.4	58.9	11	44.6	5.7	30.8	6.1	16.1	2.5	17.6	2	199.4
AC2	18	20	2	243.9	377.1	54.5	244.9	42.7	9	29.5	4	23.5	4.4	13.4	1.7	11.5	1.5	128.3
AC2	20	22	2	283.8	475.4	55.9	253.1	44.1	8.9	32.3	4.6	25.5	4.7	13.2	1.9	11.6	1.6	151.1
AC2	22	24	2	227.5	716.2	72.5	309.1	62.2	12.4	49.6	6.7	32.6	6	12.5	2	11.2	1.2	208.3
AC2	26	28	2	211.1	518.4	56.4	241.4	43.8	8.3	29.3	3.9	18.8	3.2	9.1	1	5.4	0.8	99.8
AC2	28	30	2	221.7	445.9	66.2	255.4	47	10	34.2	4.6	20	2.9	7.1	1	5.9	0.4	70.5
AC4	26	28	2	225.2	261.6	68.6	272.9	52.5	11.8	42.1	5.7	30.1	5.8	15.7	2.5	17	1.8	180.3
AC4	30	32	2	183	383.3	53.3	217	42	7.9	27.4	4	25.7	4.3	12.1	1.4	9.3	1.2	114.9
AC4	34	35	1	233.4	463.1	65.7	250.8	47.1	8.2	27.6	4.2	26.5	4.9	13.5	1.6	11.2	1.3	133.3
AC4	35	36	1	209.9	422.6	53	170.3	31.7	6.4	25	3.8	19.4	3.7	9.6	1.3	7.5	1.1	100.7
AC5	32	34	2	147.8	383.3	59.8	241.4	39.7	7.1	23.6	3.4	18.5	2.9	7.8	1	6.6	0.8	70.6
AC5	34	36	2	194.7	578.6	95	429.2	73.5	12.7	48.9	6.1	26.2	4.5	9.8	1.6	10.4	1	90.3
AC6	26	28	2	231	457	52	171.5	31.8	6	21.3	2.7	13.2	2.3	5.5	0.8	5.8	0.6	66.5
AC6	28	30	2	258	498.7	61.1	194.8	39.4	6.7	19.1	2.8	15.6	2.6	6.5	0.7	4.3	0.6	63.5
AC6	30	32	2	214.6	454.5	54	178.5	34.2	5.8	17.2	2.7	14.9	2.4	6.7	0.9	5.1	0.7	63.4
AC8	24	26	2	143.1	439.8	72.7	326.6	72.8	14.1	45.4	7.2	44.2	7.6	21.5	2.7	15	2.1	199.4
AC8	26	28	2	136	491.4	91.8	463.1	110.4	21.7	83.6	13.9	89.2	16.8	50.3	6.4	37.9	5.2	514.3
AC8	28	29	1	94.1	271.5	43.6	187.8	40.5	9.8	47.3	7.3	44.3	9.2	26	3.4	20.6	3.2	298.4
AC9	28	29	1	64	238.3	38.4	177.3	40.1	11.4	50.3	7.4	45.3	10.2	28.4	3.5	23.7	4.1	342.9
AC12	18	20	2	504.3	807.1	129.3	449.1	78.7	9.5	65.1	7.9	37.9	7	16.4	2	11.4	1.5	185.4
AC12	20	22	2	160.7	699	41.4	142.3	27.9	3.3	22.6	3.2	16.1	3.3	8	1	7.4	1.2	95.1
AC13	20	21	1	146.6	562.6	40.2	131.8	25.6	2.6	19.9	2.9	16.2	2.7	7.5	1	6.9	1	69.8
AC16	22	24	2	160.7	347.6	51.1	201.8	41.9	7	30.2	4.3	29.4	4.9	15.6	1.8	13.8	1.9	128.3

Hole ID	From (m)	To (m)	Interval (m)	La2O3 ppm	CeO2 ppm	Pr6O11 ppm	Nd2O3 ppm	Sm2O3 ppm	Eu2O3 ppm	Gd2O3 ppm	Tb4O7 ppm	Dy2O3 ppm	Ho2O3 ppm	Er2O3 ppm	Tm2O3 ppm	Yb2O3 ppm	Lu2O3 ppm	Y2O3 ppm
AC16	24	26	2	255.7	339	85.3	324.3	64.9	11.5	55.9	8.2	56.5	9	25	3.3	21.9	2.9	269.2
AC16	26	28	2	303.8	277.6	86.6	354.6	74.3	12.3	65.8	8.9	62.3	11.4	35.2	4.1	28.1	3.7	350.5
AC16	28	30	2	194.7	276.4	52.2	204.1	44.6	5.9	36.3	5.2	33.5	7.3	19.9	2.1	16.2	2.4	187.9
AC17	28	30	2	229.9	533.1	68.9	229.8	41.5	8.4	31.7	4.9	28.9	4.5	11.2	1.3	7.5	1.1	129.5
AC17	30	32	2	84.4	234.6	39.2	179.6	47.5	8.9	41	6.8	41.7	9.1	27.6	2.7	23	3.3	292.1
AC17	32	34	2	161.8	357.5	50	200.6	42.8	8	42.5	6.5	42	9.1	25.7	2.4	21	2.8	293.3
AC17	34	36	2	118.5	258	38.2	166.8	41.4	7.8	44.3	7.5	47.3	10.8	32.7	3.2	25.3	3.7	382.2
AC18	16	18	2	336.6	221.1	132.9	533	113.4	23	65.2	9.8	46	7.9	19.7	2	15.5	2	182.9
AC21	22	24	2	100.2	368.5	60.5	282.3	57.1	12.6	61.1	9	37	8.6	20.9	2.7	22.4	2.6	246.4
AC21	24	26	2	82.9	267.8	43.9	200.6	41.9	9.4	48.1	7.1	30.8	7.4	17.8	2.1	18.2	2.2	228.6
AC21	26	27	1	117.2	423.8	73.3	335.9	78.9	17.4	67.1	10.2	68.3	11.3	29.7	3.8	23.9	3.1	297.2
AC21	27	28	1	99.5	282.5	45.8	203	45.2	10.8	49.2	7.6	41.8	8	20.8	2.8	16.2	2.4	246.4
AC27	30	32	2	122	270.2	37.7	166.8	35.8	6.1	35.4	5.4	39.1	8.5	22.8	3	16.5	2.3	271.8
AC27	32	34	2	175.9	466.8	61.6	242.6	50.9	8.4	45	6.7	45.2	7.5	18.6	2.5	15.8	2.1	191.8
AC28	14	16	2	283.8	117.9	70.3	293.9	56.6	13.3	45	6.8	43.2	9.5	27.7	3	20.8	2.9	320
AC28	16	18	2	313.1	136.4	88.3	370.9	70.5	16.6	55.2	7.5	44.5	8.7	22.6	3	15.9	2.1	312.4
AC28	18	20	2	247.5	228.5	77.1	321.9	63.5	16.1	56.3	8	52.6	9.1	23.7	3.1	19.1	2.7	307.3
AC28	20	22	2	453.9	226	174	818.8	170.5	41.9	132.6	18.6	105.6	18.8	48.5	5.5	34.5	4.2	553.7
AC28	22	24	2	302.6	120.5	101.7	487.6	101.1	26.4	89.8	12.5	73.3	14.8	39	4.5	26.8	3.6	480
AC28	34	36	2	124.3	331.7	53.3	239.1	44.6	7.8	28.9	4.4	25	4.9	13.2	1.7	11	1.6	153.7
AC28	38	39	1	126.7	336.6	52.3	217	42.6	8.7	41	5.9	30.9	5.9	14.8	2.1	16.3	1.6	177.8
AC29	20	22	2	659.1	1003.6	225.9	839.8	161.2	40.4	126.8	17.8	110.6	16.6	41.2	5.2	33.6	4.4	391.1
AC29	22	24	2	206.4	976.6	72.1	271.8	54.2	13	43.3	6.7	33.3	5.9	14.5	2.2	13.2	1.3	146
AC29	24	26	2	229.9	680.5	66.2	268.3	50	11.3	41	6.6	34.1	6.5	17.7	2.9	19.1	2.2	177.8
AC29	26	28	2	457.4	782.5	163.1	646.2	122.9	27.2	101.9	15.5	76.2	13.8	35.6	5	33.5	3.2	398.7
AC29	30	32	2	248.6	238.3	88.1	342.9	66.7	15.2	59.2	8.7	46	8.5	21.5	3.5	22.5	2.2	254
AC29	32	34	2	431.6	315.7	126.9	501.6	92.8	22.9	93.9	14.7	76.2	15	38.2	5.9	38.7	4	473.7
AC30	30	32	2	276.8	525.8	64.3	212.3	35.7	6.7	25.5	3.5	15.8	2.6	5	0.8	5	0.5	60.3

Hole ID	From	To	Interval	La2O3	CeO2	Pr6O11	Nd2O3	Sm2O3	Eu2O3	Gd2O3	Tb4O7	Dy2O3	Ho2O3	Er2O3	Tm2O3	Yb2O3	Lu2O3	Y2O3
	(m)	(m)	(m)	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm
AC33	16	18	2	316.7	762.8	100.8	334.8	46.4	9.5	15.1	1.8	5.5	0.7	1.1	0.1	0.9	0.1	9.8
AC33	26	28	2	150.1	452.1	61.4	290.4	64.9	18.6	57.3	8.1	41.4	8.8	21.7	2.7	17.6	2.2	233.7
AC35	18	20	2	591.1	127.8	178.8	636.9	115	29.3	105.9	14.1	83.1	15.4	41.2	6	29.9	3.7	405.1
AC35	24	26	2	217	472.9	53.6	194.8	31.2	7.8	27.7	3.5	22	3.9	11.8	1.3	10.4	1.4	121.5
AC35	28	30	2	194.7	385.7	48.8	189	32.8	8.6	29.9	3.9	24.6	4.7	13.7	1.9	12.2	1.6	153.7
AC36	28	30	2	99.3	229.7	28.3	142.3	32	8.8	43.6	6.4	36.6	9.4	27	4.2	22.3	3.2	346.7
AC37	20	21	1	188.8	393.1	52.2	212.3	42.7	10.1	46.1	8.4	44.9	8.3	23.8	3.4	19.7	2.9	293.4
AC41	14	16	2	268.6	148.6	83.2	348.8	69.9	18	50.4	6.8	38.9	7.9	20.6	2.2	17	2.2	224.8
AC41	22	24	2	115.9	298.5	43.1	197.1	41.4	11.3	33.4	5	30.8	6.5	17	2	13.3	1.9	184.1
AC42	12	14	2	243.9	554	53.6	148.1	13	2.7	6.6	0.8	3	0.6	1.2	0.1	1	0.1	9.4
AC58	26	28	2	272.1	646.1	73.2	261.3	47.9	6.3	36.2	4.6	22.5	3.4	8.3	1	5.6	0.9	116.4
AC60	26	27	1	98.7	287.4	47.7	212.3	45.7	10.3	43	6.8	39.7	8	23.2	3.1	17.9	2.7	245.1
AC70	20	22	2	181.8	496.3	67.7	200.6	23.7	4.8	12.8	1.7	6.7	0.9	2.2	0.2	1	0.2	16.9
AC81	24	26	2	715.4	230.9	235.6	890	179.7	38.2	129.1	17.6	88.8	16.2	40.9	6.3	37.2	5.2	463.5
AC81	26	28	2	700.2	240.8	155.9	629.9	126.4	30.8	130.2	17.6	92.6	18.6	49.2	7.1	41.3	5.9	723.8
AC89	16	18	2	476.2	195.3	119.1	408.2	47.7	8.8	16.9	1.9	5.7	0.8	1.6	0.2	1.6	0.2	15.1
AC89	26	28	2	430.4	332.9	115.3	454.9	90.8	23.2	85	12.2	65.9	13.4	38.4	4.9	31	5.1	429.2
AC89	28	30	2	215.8	299.7	67.1	279.9	60.8	14.7	52.3	7.1	39.1	7.8	21.4	3	17.6	3.1	226
AC89	30	32	2	136	334.1	46.4	192.5	45.3	9.9	41.5	5.8	29.4	5.7	15.9	2	13.4	2.2	160
AC90	32	34	2	197	163.4	77.9	324.3	71	20.8	55.7	8.6	49.4	9.9	31	4.3	28.2	4.7	285.7
AC90	34	36	2	164.2	113.4	62.8	279.9	64.8	18.8	56.5	8.3	45.6	8.7	25.4	3.7	25.7	4.3	209.5
AC101	22	24	2	170.1	244.5	58.4	253.1	51.3	14.6	55.6	8.3	40.5	7.9	20.5	2.8	15.5	2.2	248.9
AC101	24	25	1	179.4	224.8	67.9	256.6	51	1.8	37.3	5.2	35.6	6.5	16.7	2.1	8.1	1.5	190.5
AC104	26	28	2	133.7	235.9	42.5	192.5	40.4	11.6	47.6	7	38.1	8.5	24.7	3.1	18.3	2.7	326.4
AC104	28	30	2	168.9	307.1	51.5	221.6	44.3	12.2	42.7	6.1	29	5.9	16	2.1	11.7	1.8	222.2
AC110	22	24	2	336.6	359.9	97.1	376.7	75.7	17	65.8	10.1	50.2	9.9	25.4	3.5	20.8	3.1	275.6
AC110	28	29	1	161.8	414	49.9	215.8	47.4	10.5	47.3	7.2	36.2	7.8	19.8	2.7	15.3	2.2	248.9

	From	To	Interval	La2O3	CeO2	Pr6O11	Nd2O3	Sm2O3	Eu2O3	Gd2O3	Tb4O7	Dy2O3	Ho2O3	Er2O3	Tm2O3	Yb2O3	Lu2O3	Y2O3
Hole ID	(m)	(m)	(m)	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm
AC111	22	24	2	231	258	62.8	228.6	42.1	8.7	34	4.7	24	4.8	12.5	1.7	10.5	1.5	143.5
AC112	21	23	2	232.2	175.7	83	359.3	76.1	20.5	71.8	10.3	53.3	10.9	27.4	3.9	24.4	3.5	330.2
AC115	26	28	2	463.3	409.1	125.7	433.9	87	14.9	67.9	9.8	49.7	8.5	23	3.5	22.1	3.2	200.6
AC115	28	29	1	336.6	308.3	80.7	298.6	58.4	11	61.7	9.7	57.3	11.8	35.6	5.5	34.8	5.4	323.8
AC119	18	20	2	225.2	557.7	58.5	214.6	33.5	4.9	14.6	1.9	7.6	1.1	2.4	0.3	1.4	0.1	24.3
AC122	18	20	2	363.6	875.8	119	461.9	84.4	16.9	61.6	8.6	40.1	6.6	16.2	2.2	12.2	1.6	184.1
AC123	15	17	2	266.2	604.4	61.4	207.6	29.6	5.7	15.2	1.8	7.4	1	2.3	0.3	1.5	0.2	25.9
AC129	21	23	2	467.9	972.9	88.7	248.4	41.3	6.8	26.9	3.6	15	2	4.2	0.5	2.3	0.3	49.4
AC130	20	22	2	109.2	773.9	44.1	148.1	29.9	5.5	20.1	3.3	16.8	2.5	5.8	0.7	4.9	0.5	46.5
AC130	32	34	2	147.8	398	47.6	186.6	35.8	6.3	29.3	4.3	21.9	4	9.5	1.4	8.9	1.1	110.6
AC131	23	25	2	198.2	545.4	62.2	166.8	10.4	1.6	4.3	0.6	1.9	0.3	0.8	0.1	0.7	0.1	6.7
AC134	14	16	2	265.1	797.2	91.9	314.9	44.9	9.8	25.2	3.1	13	1.7	3.2	0.4	2	0.2	29.1
AC136	18	20	2	156	398	68.9	291.6	59.1	11.5	55.2	7.8	43.2	9.1	23.4	3.6	23	3.3	303.5
AC137	17	19	2	236.9	126.5	70	264.8	48.5	12.3	40.3	5.1	27.2	5.3	13.6	2	12.3	1.7	157.5
AC137	25	27	2	67.9	187.9	29.4	159.8	49.3	14.8	68.7	10	58.2	12.5	32.6	5	30.5	4.5	401.3
AC142	16	18	2	283.8	761.6	94.4	309.1	36.6	5.8	14.1	1.7	5.6	0.6	1.1	0.1	0.8	0.1	10.7
AC175	12	14	2	262.7	609.3	56.7	186.6	37.7	7.5	27.7	4.1	18.8	3.4	6.4	0.9	4.7	0.5	59.4
AC179	16	18	2	283.8	599.5	97.9	403.6	96	14.4	92.9	13.4	80.1	14.1	40.4	5.4	33.8	4.4	396.2
AC179	18	20	2	228.7	250.6	49.9	197.1	42.4	6.1	45.4	6.4	35.9	7.2	21.5	3	17.4	2.7	262.9
AC181	17	19	2	299.1	227.3	90.9	327.8	60.9	9.5	44.3	6.2	31.9	5.9	15.9	2.8	14.8	2	144.8
AC181	23	25	2	234.6	373.4	52.9	186.6	31.9	6.5	25	3.5	16.6	3	8.1	1.2	6.7	0.9	93.7
AC184	22	24	2	199.4	464.3	61.9	217	35.9	6.9	24.6	3.1	14.4	1.9	4	0.5	2.2	0.4	40.6
AC192	31	32	1	222.8	595.8	70.4	306.8	64.6	14	56.9	7.9	41.3	7.1	17.7	2.3	14.1	1.7	194.3
AC194	22	24	2	168.9	87.3	69.8	290.4	64.1	18.1	52.3	7.8	43.8	9	23.1	3.6	23.1	3.3	231.1
AC196	29	31	2	213.4	143.7	64	284.6	54.4	16	64	8	40.6	9.4	30	3.7	17.4	3	488.9
AC198	41	43	2	312	197.8	89	347.6	69.6	16	57.6	8.1	41.4	8.2	21.5	3	17.5	2.5	245.1

	From	To	Interval	La2O3	CeO2	Pr6O11	Nd2O3	Sm2O3	Eu2O3	Gd2O3	Tb4O7	Dy2O3	Ho2O3	Er2O3	Tm2O3	Yb2O3	Lu2O3	Y2O3
Hole ID	(m)	(m)	(m)	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm
AC200	20	22	2	228.7	422.6	110.9	576.2	149.6	46	169.4	24.1	138.9	27.6	70	10.3	59.3	8.9	826.7
AC200	22	24	2	118.5	162.1	62.1	352.3	96.2	34	149.8	21.2	132	28.3	73.8	11.2	63	10.2	1002
AC201	32	34	2	572.3	287.4	205.4	834	167	44.9	144.1	20.4	107.7	19.9	51.3	7.7	46.7	7	552.4
AC212	24	26	2	412.8	699	152.2	618.2	126.4	29.5	91.8	12.7	63.6	10.9	25.6	3.8	22.1	3.1	290.8
AC212	26	28	2	301.4	313.2	97.1	388.4	74.4	17.5	56.7	7.4	36.5	6.4	15.6	2.2	13	1.9	185.4
AC213	21	23	2	208.8	200.2	83.1	328.9	70.9	18.2	59.1	8.4	43.7	7.5	17.5	2.7	16.5	2.2	177.8
AC213	23	25	2	197	152.3	60.2	241.4	49.1	13.9	48.3	6.8	36.7	6.8	16.8	2.5	15.7	2.2	181.6
AC221	17	19	2	1055.5	2014.6	293.6	1117.4	213.4	58.8	172.9	23.4	110	19.7	50.8	6.5	39.1	5.7	506.7
AC221	19	21	2	578.2	931.1	136.5	519	97.6	27.8	90	11.9	59.8	11.4	28.9	3.8	21.4	3.1	322.6
AC223	17	19	2	274.4	269	88.7	341.8	59.7	13.4	40.5	5.5	28.9	5.5	16.2	2.5	15.9	2.5	144.8
AC223	19	21	2	319	352.6	105	466.6	85.8	20.8	73.4	9.4	50.4	9.6	27.3	3.9	24	3.7	252.7
AC223	23	25	2	245.1	626.5	70.3	303.3	60.9	14.8	57.6	7.7	41.2	7.9	22.6	3	17.1	2.7	250.2
AC223	25	27	2	221.7	826.7	62.5	272.9	52.8	13.6	61.3	8.2	49.4	10.7	31.9	4.2	24.6	4	417.8
AC225	16	18	2	262.7	344	90.9	312.6	59	7.7	34.7	5	23.3	3.6	9.7	1.5	9.7	1.3	72.6
AC225	18	20	2	246.3	476.6	80	279.9	57.5	8	40.7	6.3	33.4	6.4	17.8	2.7	15.8	2.3	175.2
AC225	20	22	2	219.3	508.6	59.2	203	40.1	6.2	29.3	4.5	23.1	4.4	12.7	1.9	12.1	1.7	147.3
AC225	22	24	2	163	543	41	135.3	23.8	3.5	15.8	2.3	12.2	2.2	6.1	1	6	0.9	60.7
AC225	24	26	2	1290.1	749.3	512.3	1819.6	402.4	52.7	259.3	38.3	192.8	31.6	79.4	11.9	69.6	9.3	692.1
AC225	26	28	2	1430.8	540.5	624.6	2297.8	514.9	67.5	317	48.9	244.5	40.7	105	16.2	100.1	12.9	861
AC225	28	30	2	738.9	283.8	277.9	1074.3	249.3	37.2	210.9	32.7	179	33.1	91.1	14.4	87.9	12.3	787.3
AC225	30	32	2	837.4	301	233.2	958.8	185.5	31.8	216.7	27.2	152.6	31.6	77.1	12	67.8	9.9	840.7
AC225	32	34	2	475	316.9	141.4	562.2	108	18.8	119.9	15.4	85	17.3	42.3	6.9	41.4	5.8	458.4
AC225	34	35	1	500.8	534.4	128.1	526	103.6	21.4	129.1	16.1	90.4	19.1	48.7	7.5	43.4	6.3	607
AC226	26	28	2	394.1	275.2	86.3	324.3	64.6	12	59.2	8.6	47.2	8.5	23.3	3.4	19.9	2.9	254
AC226	28	30	2	611	318.2	165.5	638	134.5	26.4	132.6	19.4	103	18.3	50.4	7.4	43.3	5.9	519.4
AC226	30	32	2	229.9	237.1	51.4	196	37.6	7.7	36.3	5.4	27.5	5.1	14.2	2.1	11.8	1.9	144.8
AC226	46	48	2	36.7	180.6	34.3	199.5	50.8	12.4	67	11.1	68.2	14.6	46.7	7	41.3	6.7	515.6
AC232	18	20	2	235.7	394.3	76.4	254.3	42.3	9.5	20.6	2.4	9.3	1.4	3.4	0.4	2.7	0.4	33.3

	From	To	Interval	La2O3	CeO2	Pr6O11	Nd2O3	Sm2O3	Eu2O3	Gd2O3	Tb4O7	Dy2O3	Ho2O3	Er2O3	Tm2O3	Yb2O3	Lu2O3	Y2O3
Hole ID	(m)	(m)	(m)	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm
AC232	20	21	1	274.4	396.8	82.3	278.8	47.3	11.1	25.6	3	11.9	1.8	4.5	0.6	3.9	0.5	49.1
AC232	21	23	2	391.7	277.6	104.2	365.1	63.8	15.1	36.9	4.4	18	2.7	7.4	1.1	5.8	0.8	81.5
AC235	25	27	2	159.5	233.4	42.9	170.3	36.6	10.3	39	6.3	32.1	7.2	20.6	2.8	15	2.4	266.7
AC244	22	24	2	234.6	121.6	97.9	495.7	107.5	28.4	85.6	10.7	51	9.9	24	3.2	18.1	2.4	293.3
AC244	26	27	1	212.3	454.5	53.2	193.6	36.8	9	27.1	3.7	16.9	3	7	0.9	4.6	0.6	76.1
AC245	26	27	1	252.2	673.2	72.1	233.3	39.1	7	21.4	2.8	10.9	1.6	3.1	0.3	1.8	0.2	27.8
AC246	18	20	2	201.7	336.6	72.1	296.3	63.3	16.6	48.1	6.7	33.3	6.2	16.4	2.2	15.1	2.1	174
AC263	20	22	2	463.3	186.7	176.4	718.5	167	26.6	139.5	20.7	104.7	19	51.3	6.9	42.8	6.5	501.6
AC263	22	24	2	233.4	180.6	53.6	200.6	39.7	7.8	38	5.7	30.3	6.2	16.7	2.6	16.1	2.5	193
AC265	32	34	2	144.3	272.7	52.2	192.5	47	12.3	51.9	7.3	47.7	10.9	30.3	4.4	27.3	3.9	351.8
AC265	38	40	2	154.8	659.7	52.2	164.5	34.7	8.3	27.7	3.3	17.7	3.3	7.9	1	5.8	0.7	92.3
AC268	26	28	2	360	501.2	129.3	554	124.1	34.3	118.7	16.4	80.3	14.8	35.1	4.9	26.6	3.8	509.2
AC269	12	14	2	340.1	597	88.1	321.9	53.2	12.2	33.1	3.7	16.5	2.8	6.6	0.9	4.7	0.6	97.7
AC269	14	16	2	328.4	815.7	83.6	306.8	51.4	11.6	29.3	3.2	14.1	2.1	4.5	0.6	3.1	0.4	58.5
AC269	18	20	2	241.6	784.9	61.6	229.8	36.8	8.2	21.6	2.4	9.8	1.6	3.5	0.4	2.2	0.3	41.9
AC269	22	24	2	259.2	458.2	70.9	253.1	42.9	9.5	22.9	2.6	10.6	1.7	3.8	0.6	3.5	0.5	51.9
AC274	16	18	2	209.9	659.7	63.1	229.8	46.7	6.8	39.1	5.7	33.3	5.8	13.8	2.4	14.1	1.9	174
AC274	18	20	2	199.4	238.3	62.6	241.4	52.6	6.5	43.1	6.5	38.5	7.1	18.1	2.9	18.4	2.5	218.4
AC274	20	22	2	376.5	152.3	141.4	557.5	118.3	15.2	98.8	14.5	84.9	15.1	38.7	6.1	37.5	5.5	454.6
AC274	22	24	2	286.2	359.9	92.9	373.2	81.8	11.8	72	10.6	63.7	11.6	28.2	4.4	26.8	3.8	370.8
AC274	24	26	2	212.3	201.5	62.6	248.4	51.5	7.5	49	7.4	44.1	8.2	20.7	3.3	20.5	2.8	276.8
AC274	26	28	2	183	219.9	58.4	221.6	47.1	6.9	42.2	6.1	36.5	6.7	16.9	2.6	16.4	2.4	209.5
AC274	32	34	2	213.4	481.5	59.9	235.6	50	7.8	49.2	7.1	41.2	7.5	18.3	2.8	16.4	2.3	243.8
AC275	19	21	2	939.4	1351.2	224.7	684.7	104.7	12.3	43.8	5.3	23.6	3.3	8.3	1.2	7.4	1.1	80.6
AC275	23	25	2	63.1	410.3	25.9	120.1	34.3	6	38.6	6.1	40.5	7.9	24.8	3.5	21.3	3.2	229.9
AC275	25	27	2	66.1	570	34.4	159.8	46.5	8.8	51.8	8.3	53	9.3	27.6	3.9	25.2	3.7	256.5
AC275	27	29	2	211.1	107	65.7	298.6	79.2	15.4	106.6	16.2	103.4	20.4	62	8.2	46.1	7	784.8

	From	To	Interval	La2O3	CeO2	Pr6O11	Nd2O3	Sm2O3	Eu2O3	Gd2O3	Tb4O7	Dy2O3	Ho2O3	Er2O3	Tm2O3	Yb2O3	Lu2O3	Y2O3
Hole ID	(m)	(m)	(m)	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm
AC275	29	31	2	283.8	190.4	80.5	348.8	77.8	14.2	90.8	12.9	81.5	16	49.4	6.5	37.7	6	643.8
AC275	31	33	2	124.3	65.2	34.7	148.1	35.3	7	46.9	7.1	48.7	9.6	30.5	4	22.7	3.5	417.8
AC279	31	33	2	459.7	208.8	154.7	622.9	121.8	31.3	110.8	15.4	76.7	15.9	44.7	5.6	32.1	5.1	515.6
AC279	33	35	2	478.5	211.3	130.5	527.2	107	29.4	115.3	16.7	87.7	19.2	55.9	7.1	40.7	6.8	718.8
AC279	35	37	2	217	223.6	63.7	260.1	53.9	13.3	51.3	7.4	39.6	7.9	23.9	3.3	18.3	2.9	264.1
AC280	20	22	2	273.3	366.1	88.6	367.4	75.1	19.8	76.1	11.2	59.7	12	34.1	4.6	26	4.3	369.5
AC281	22	24	2	302.6	449.6	84.9	276.4	51	12	37.5	5	25.3	4.4	11.2	1.6	9.1	1.3	139.7
AC281	26	28	2	175.9	443.5	62	211.1	33.2	7.5	22.5	2.9	14.5	2.3	6	0.9	5	0.8	70.1
AC282	21	23	2	174.7	298.5	67.8	289.3	58.3	14.6	39.4	4.6	22.7	3.5	8.9	1.3	8.2	1	93.7
AC286	13	15	2	153.6	835.3	37.2	129.5	23.4	5.8	14.3	1.7	7.8	1.2	3.1	0.5	2.5	0.3	39.6
AC287	20	22	2	312	614.2	63	203	34.1	8	17.8	2.3	8.9	1.3	2.7	0.4	2.2	0.3	30
AC287	24	26	2	369.4	515.9	99	366.2	63.9	16.7	42.9	5.3	23	3.8	9.5	1.1	6.9	0.9	96.6
AC289	17	19	2	194.7	286.2	61	242.6	46.5	13	38.5	5.2	28.1	4.8	13.2	1.9	12.3	1.7	134.6
AC289	25	27	2	190	474.2	65.5	239.1	42.4	10.6	30.3	3.9	21.9	4.2	12.1	1.5	9.3	1.4	147.3
AC292	21	23	2	160.7	590.9	49.5	196	40.2	11.4	29.4	3.9	16.4	2.3	4.6	0.5	2.5	0.3	37.7
AC292	27	29	2	364.7	464.3	101.5	347.6	58.7	15.3	38.2	5	20.7	3.2	6.6	0.8	4.4	0.6	62.5
AC295	19	21	2	330.7	377.1	92.6	337.1	56.4	14	37.1	4.9	22.8	4.4	10.9	1.7	10.6	1.5	119
AC301	22	24	2	227.5	491.4	68.9	228.6	43.6	10.7	25.5	3.3	11.9	1.7	3.4	0.4	2.6	0.3	36.1
AC301	26	28	2	143.1	386.9	58.5	233.3	48	10.6	24.1	3.2	14.8	2.4	6.6	1	7.4	1.1	60.1
AC302	26	28	2	679.1	746.9	270.6	1018.3	190.2	44.4	109	13.3	56.9	9.6	24	3.4	21	3.1	265.4
AC302	28	30	2	221.7	281.3	80.7	317.3	60	15.3	38.3	4.7	20.8	3.9	10.5	1.4	8.5	1.4	141
AC305	23	25	2	208.8	224.8	67.9	267.1	54.3	13.3	54.1	7.8	44	8.3	23.8	3.3	20.3	2.7	269.2
AC306	19	21	2	286.2	264.1	101.1	426.9	92.5	20.4	78.6	10.7	56.4	9.5	26	3.5	21.5	2.8	236.2
AC309	31	33	2	174.7	364.8	52.7	201.8	41	6.4	36.2	5.3	29.5	5.6	16.5	2.3	14.9	2.1	179.1
AC309	35	37	2	208.8	232.2	58.8	234.4	47.1	9.3	44.1	6.6	37.6	7.3	22.4	3.3	20	3.1	238.7
AC311	14	16	2	455	407.8	42.7	94.4	7.8	1.5	3.9	0.5	2.1	0.3	0.9	0.1	0.7	0.1	9.9
AC312	38	40	2	172.4	321.8	39	162.1	31.4	8.1	36.2	4.7	28.5	5.3	15.6	1.8	10	1.7	212.1

	From	To	Interval	La2O3	CeO2	Pr6O11	Nd2O3	Sm2O3	Eu2O3	Gd2O3	Tb4O7	Dy2O3	Ho2O3	Er2O3	Tm2O3	Yb2O3	Lu2O3	Y2O3
Hole ID	(m)	(m)	(m)	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm
AC312	40	42	2	168.9	238.3	33.5	150.5	32.4	10.4	47.5	6.2	38.9	8	24.5	2.8	13.6	2.4	381
AC321	38	40	2	192.3	48.4	65.7	316.1	79.1	28.5	127.9	19.1	110.3	25.2	67.9	9.9	52.4	8.5	1048.9
AC321	40	41	1	293.2	63.8	77.3	370.9	85.3	29.8	133.7	18.8	107.7	24.3	65.6	9.4	51.1	8.3	998.1
AC322	25	27	2	227.5	341.5	77.5	306.8	59	17.1	47	6.2	29.8	5.6	14.1	1.9	11.5	1.6	191.8
AC322	27	29	2	201.7	117.9	55.2	233.3	46.6	15.2	50	6.6	34.2	6.9	18	2.5	14.2	2.1	243.8
AC324	24	25	1	680.2	185.5	212.6	841	164.7	46	145.2	18.6	94.9	17.6	46.9	6.3	36	5.3	544.8
AC326	34	36	2	485.5	442.2	167.9	719.7	143.8	43.3	148.7	21.8	115.9	23.1	66.2	9.2	53.1	8.4	746.7
AC328	30	32	2	243.9	156	77.9	342.9	66.2	21.8	70.1	8.9	49.8	10.7	31.2	4.5	25.6	3.9	420.3
AC343	24	26	2	193.5	351.3	70.9	274.1	55.5	13.1	40.8	5.7	26.6	4.7	11.9	1.6	9.3	1.3	94.7
AC343	26	28	2	600.5	169.5	161.9	670.7	131	34.3	138.3	18.8	96.4	20.7	57.5	7.9	47.4	7.4	590.5
AC344	26	28	2	333.1	1202.6	94.4	373.2	66.9	12.6	51.9	7.5	39.6	6.7	17.6	2.6	16.3	2.4	189.2
AC344	28	30	2	254.5	786.2	70.9	289.3	50	9.1	28.4	3.7	16.6	2.7	6.4	1	6.4	0.9	74
AC344	32	34	2	129	514.7	47	196	40.5	9.9	39.9	6.4	37.1	7	17.6	3	18.4	2.7	200.6
AC350	19	21	2	235.7	610.5	66.1	257.8	49.4	9.6	33.3	4.4	19.6	2.8	6.9	0.8	4.6	0.5	65.4
AC354	19	21	2	269.7	598.2	104.6	386.1	78	18.9	60.1	8.7	45.2	9	24.2	3.5	21.3	3.1	283.2
AC354	27	29	2	287.3	316.9	84.7	334.8	69.2	15.3	70	9.8	51.5	9.9	27.8	4.2	24.7	3.7	301
AC356	30	32	2	236.9	102.4	71.2	320.8	71.1	21.8	86.7	11.8	65	13.9	36.3	5	28.8	4.3	513
AC356	32	34	2	362.4	168.3	140.2	620.5	151.9	46.1	175.2	25.1	142.3	29.8	79.6	11	60.5	9.3	1108.6
AC359	16	18	2	1156.4	902.9	443.4	1807.9	276	38.1	105.8	11.9	36.3	3.7	6.1	0.6	3.5	0.4	46.5
AC359	22	24	2	253.3	561.4	105.1	447.9	82.8	14.4	41	4.9	17.9	2.1	4.1	0.5	3.2	0.4	29.8
AC360	27	29	2	572.3	498.7	177.6	696.3	140.3	27.4	111.3	15.4	76.4	13.8	34.7	5	32	4.3	350.5
AC360	29	31	2	561.8	267.8	221.1	957.6	206.4	46.7	182.1	26.5	138.9	27.3	73.1	10.3	64.1	9.2	815.3
AC360	31	33	2	354.2	244.5	131.7	606.5	153.1	45	215.5	32.5	192.8	43.3	122.4	16	92.5	14.3	1777.9
AC360	33	35	2	286.2	167.1	95.3	422.2	90.8	23.4	92.9	13.3	70.2	14	38	5.2	31.1	4.6	466.1
AC361	22	24	2	136	367.3	48.1	186.6	45.3	6	41.3	7.3	47.4	9.4	28.4	4.5	32.9	4.9	217.2
AC361	24	26	2	554.7	409.1	149.8	615.9	147.3	19	181	27.8	165.3	36.3	110.2	15.3	94.9	15.1	1253.4
AC363	34	36	2	192.3	296	67.2	263.6	56.9	10.4	53.6	7.9	44.2	8.1	23.3	3.2	20.8	3.1	212.1

	From	To	Interval	La2O3	CeO2	Pr6O11	Nd2O3	Sm2O3	Eu2O3	Gd2O3	Tb4O7	Dy2O3	Ho2O3	Er2O3	Tm2O3	Yb2O3	Lu2O3	Y2O3
Hole ID	(m)	(m)	(m)	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm
AC363	36	38	2	589.9	254.3	160.7	702.2	153.1	31.5	184.4	27.3	159.5	32.4	93.8	12	74.8	11.4	1123.9
AC366	31	33	2	180.6	507.3	48.6	164.5	27	6.2	16.8	2.1	10.4	1.5	4.1	0.5	2.6	0.4	37.6
AC374	32	34	2	173.6	374.7	46.5	193.6	45.7	13.8	54.4	8.4	49.4	10.5	27.9	4.2	24.5	3.8	345.4
AC382	17	19	2	432.8	235.9	149.8	541.2	101.2	19.9	70.7	10.3	50	9	23.4	3.7	23.6	3.4	214.6
AC387	30	32	2	302.6	207.6	78.9	282.3	54.6	12	51.9	7.2	39.3	7.1	17.5	2.6	16.1	2.4	229.9
AC387	32	34	2	350.7	179.3	83.1	316.1	57.7	13.9	58.4	8.3	45.9	8.7	22	3.3	19.4	3	301
AC387	36	38	2	233.4	592.1	80.2	338.3	72.5	18.1	66.2	9.4	48.7	8.3	19.6	3	17.8	2.5	274.3
AC388	21	23	2	199.4	663.3	71	307.9	67.3	18.1	66	9.6	50.3	11.2	26.5	4.2	26.5	4	336.5
AC389	22	24	2	72.7	281.3	45.6	215.8	50	13.6	46.9	7.1	35.7	7.8	17	2.6	15.7	2.3	223.5
AC391	28	30	2	634.5	223.6	183.7	718.5	138	29	127.9	17.9	89.5	18.2	42.7	6.7	39.7	5.6	532.1
AC396	20	22	2	562.9	552.8	153.4	584.4	118.3	19.3	86.8	11.8	60	11	28.1	4.5	25.2	3.8	303.5
AC406	16	18	2	209.9	557.7	54.6	156.3	11.1	2.5	3.5	0.3	1.1	0.2	0.5	0.1	0.5	0.1	3.9
AC409	21	23	2	192.3	543	49.4	171.5	28.5	5.2	19.6	2.9	12.9	2.4	5.6	0.8	5.6	0.8	70.1
AC411	23	25	2	334.2	184.3	90.9	374.4	75.7	8.2	74	11	54.6	11.5	27.8	4.2	25.3	3.5	358.1
AC412	18	20	2	784.6	405.4	287.6	1140.7	258.6	36.6	215.5	28.9	153.8	26.9	69.1	9.6	58.6	6.6	604.5
AC412	22	24	2	192.3	426.3	51.4	199.5	39.2	7.2	37.9	4.7	26.9	5.5	14.9	2.1	12.1	1.6	182.9
AC413	21	23	2	130.2	199	39.9	166.8	35.9	6.7	41.5	5.5	33.6	8.4	25.4	3.7	22.1	3.4	313.7
AC415	13	15	2	365.9	222.3	98.8	382.6	79.8	6.1	73.7	10.4	60.8	12.4	31.8	5	29.8	4.3	359.4
AC415	15	17	2	312	259.2	88.7	337.1	74.7	5.7	68.5	10	59.7	11.9	32.7	4.9	32.1	4.7	369.5
AC417	25	27	2	232.2	129	67.5	264.8	59	4.2	50	7.3	42	8	20.9	3.2	20.5	2.9	221
AC417	27	29	2	256.8	143.7	62.3	251.9	54.5	4.6	63.2	8.8	54.1	11.6	31	4.7	27.6	4.1	396.2
AC418	21	23	2	297.9	815.7	94.2	328.9	66.2	5.1	43.3	5.8	30	5	11.9	1.8	10.9	1.4	112.5
AC418	23	25	2	436.3	662.1	98.8	377.9	77.6	6.8	72.8	10.5	61.8	12.6	31.9	4.9	29.7	4.3	393.7
AC419	34	36	2	119.6	221.1	39.8	178.5	38.2	8.9	45.8	6.4	41.8	9.3	28.8	4.1	26.3	4.2	303.5
AC424	9	11	2	242.8	142.5	95.5	402.4	62.5	12.3	27.1	3.2	10.4	1.4	2.3	0.3	1.9	0.3	25.1
AC424	11	13	2	502	309.6	281.5	1504.7	286.4	57.7	118.7	13.2	42.4	5.2	7.6	1	5.8	0.6	72.8
AC424	21	23	2	262.7	288.7	107.1	494.6	118.3	31.4	105.4	14.6	70.9	13.6	30.5	5.1	35.8	4.4	384.8

	From	To	Interval	La2O3	CeO2	Pr6O11	Nd2O3	Sm2O3	Eu2O3	Gd2O3	Tb4O7	Dy2O3	Ho2O3	Er2O3	Tm2O3	Yb2O3	Lu2O3	Y2O3
Hole ID	(m)	(m)	(m)	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm
AC424	23	25	2	272.1	486.4	93.3	407.1	86.3	23.2	83.1	11.6	56.4	11.5	27.2	4.4	28.9	3.9	388.6
AC429	29	31	2	157.2	361.1	47.2	191.3	36.4	8.4	35.4	5	27.4	6.2	15.2	2.7	19.1	2.8	213.3
AC430	19	21	2	180.6	269	80.4	347.6	82.7	20.6	73.7	11.2	55.1	10.4	25.8	4.1	25.7	3.6	274.3
AC431	34	36	2	130.2	442.2	47.5	178.5	37.6	7.5	33.5	5.3	32.8	6.4	18.2	2.7	16.5	2.6	213.3
AC433	18	20	2	212.3	416.4	45.9	161	28.8	6.4	23.1	3.1	15.7	3.1	8.8	1.2	8.2	1.2	103.4
AC433	20	22	2	164.2	386.9	47.6	175	33	7.5	28.6	3.9	20.3	3.8	10.4	1.5	8.5	1.3	125.2
AC433	24	26	2	106	373.4	59.8	249.6	43.1	10.3	39.9	5.6	31	6.5	18.9	2.6	15.7	2.4	231.1
AC440	16	18	2	116.2	243.2	46.9	182	37	8	34.6	5.9	37.5	8.6	25.2	3.7	21.3	3.3	297.2
AC440	18	20	2	363.6	416.4	153.4	625.2	124.1	27.3	109.6	17.3	101.6	21	55.7	7.9	45.1	6.8	619.7
AC440	20	22	2	533.6	393.1	194.5	828.1	158.9	33.9	148.7	22.4	124	25.1	65	8.5	48.4	7	793.7
AC441	10	12	2	297.9	793.5	73.5	297.4	59.4	11.1	40.6	5.5	23.8	3.5	6.3	0.7	4.2	0.4	59.4
AC445	17	19	2	588.7	229.7	206.6	797.8	146.1	37.8	112.8	12.5	61.3	10.9	29.6	3.5	21.7	2.9	369.5
AC446	22	24	2	214.6	744.4	63.4	217	35.7	8.4	21.2	2.6	11.3	1.7	4.1	0.6	4.1	0.5	46.7
AC446	24	26	2	314.3	1449.5	95.8	351.1	57.3	12.7	33.1	3.9	16	2.4	5.3	0.8	4.1	0.6	62.4
AC446	26	28	2	219.3	691.6	60.3	217	36.8	9.1	25.6	3.3	14.6	2.5	6.3	0.9	5	0.7	78.1
AC446	28	30	2	201.7	627.7	54.7	198.3	34.2	8.7	23.7	2.7	12.4	2	4.7	0.6	3.5	0.5	51.9
AC447	21	23	2	233.4	318.2	72.6	281.1	53.3	14.2	38.3	5	23.4	4.1	10.6	1.5	9.2	1.3	122.3
AC452	21	23	2	209.9	562.6	76.8	278.8	47.7	11.3	29.5	3.9	18.6	3.4	9.6	1.6	12.2	1.6	64.9
AC452	23	25	2	199.4	406.6	74.7	271.8	48	11.7	29.2	4	19.1	3.4	9.9	1.6	11.7	1.6	68.6
AC453	24	26	2	49.8	235.9	17.6	90.5	25.5	8.5	53.4	8.3	57.3	15.4	47.1	7.1	40.3	6.4	563.8
AC455	16	18	2	388.2	259.2	92.2	321.9	47.9	11.3	30.1	2.9	11.5	1.9	4.6	0.6	3.2	0.5	58.2
AC458	37	39	2	228.7	589.6	69.4	244.9	40.2	9.1	23.9	2.6	9.9	1.6	3.9	0.5	3	0.4	53.6
AC458	39	41	2	236.9	423.8	63	233.3	36.6	8.2	23.4	2.4	10.2	1.7	4.5	0.5	3	0.5	58.2
AC467	23	25	2	432.8	191.6	102.7	346.4	47.9	11.3	27.9	3	11	1.9	3.9	0.6	3.2	0.4	54
AC467	27	29	2	636.8	187.9	157.1	534.2	83.5	19.8	47	5.5	20.7	3.3	7.8	1.4	6.1	0.8	99.3
AC467	29	31	2	676.7	174.4	154.7	528.4	83.8	21.4	53.1	6.1	24.7	4	9.3	1.3	6.6	0.9	120
AC467	33	35	2	368.3	146.2	79.7	278.8	46.4	12.6	34.6	4.3	17.2	2.9	7.2	1	5.6	0.8	99.1

	From	To	Interval	La2O3	CeO2	Pr6O11	Nd2O3	Sm2O3	Eu2O3	Gd2O3	Tb4O7	Dy2O3	Ho2O3	Er2O3	Tm2O3	Yb2O3	Lu2O3	Y2O3
Hole ID	(m)	(m)	(m)	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm
AC467	37	39	2	334.2	191.6	61	214.6	38.6	11.4	34.2	4.1	18	3.2	7.5	1	5.5	0.8	106.2
AC468	15	17	2	333.1	190.4	100.4	348.8	50	11	24.3	2.9	10	1.5	3.1	0.3	1.8	0.2	37.1
AC468	25	27	2	254.5	395.5	70.6	257.8	42.2	8.8	22.4	2.6	10.4	1.6	3.8	0.5	3.4	0.5	47.1
AC468	27	29	2	463.3	267.8	119.4	467.7	83.6	22	53	6.7	28.9	4.8	12.1	1.5	10.6	1.4	149.8
AC468	29	31	2	328.4	181.8	72.7	292.8	52.8	16	48	6.2	30.1	5.7	15	2	12.4	1.8	224.8
AC468	31	33	2	343.6	1253	126.9	495.7	86	19.5	48.8	6.4	29.6	5.2	13.5	1.7	11.4	1.5	187.9
AC469	31	33	2	178.3	432.4	51	210	35.3	8.6	24.1	3	12.1	2	4.7	0.6	3.6	0.5	57.5
AC470	22	24	2	424.6	146.2	88.2	312.6	51	13.7	40.1	5.1	21.2	3.8	9.3	1.1	6.7	0.9	144.8
AC471	18	20	2	302.6	218.7	97.4	354.6	64.8	16.9	42.9	5.9	25.7	4.2	10.1	1.2	7.7	1	122.8
AC471	20	22	2	614.5	368.5	172.8	678.8	116	31.2	87.7	11.6	49.7	8.4	20	2.3	12.6	1.7	314.9
AC471	22	24	2	330.7	191.6	84.5	320.8	55	14.6	43	5.6	24.9	4.4	11	1.2	7.1	0.9	167.6
AC472	21	23	2	140.7	243.2	40.4	175	40.2	12	58.2	9.6	59.5	13.2	38.7	4.9	29.3	4.5	561.3
AC473	9	11	2	336.6	1029.4	118.3	454.9	85.8	21.1	54.8	7.1	28.8	5	11.4	1.7	10.1	1.4	152.4
AC473	11	13	2	219.3	382	60.9	227.4	39.9	9.7	26.7	3.2	12.5	2.2	5	0.7	4.6	0.6	65.8
AC473	13	14	1	190	425	55.3	204.1	34.9	8.4	21.4	2.6	10.3	1.7	3.9	0.6	3.4	0.5	52.8
AC487	18	20	2	273.3	888.1	83.1	337.1	58.1	14.4	37	4.7	19.5	3.4	8.8	1.2	7.9	1.1	111.9
AC487	20	22	2	777.6	2248	217.5	902.8	157.7	42.4	131.4	16.2	72	14.1	37.1	5.4	32	5.1	533.4
AC487	22	24	2	173.6	520.8	49.1	199.5	34.8	8.7	22.9	2.8	12.2	2.2	5.7	0.8	5	0.8	87
AC492	15	17	2	198.2	746.9	52.8	183.1	30	7.3	19.4	2.4	10.6	1.9	4.6	0.6	3.9	0.6	56.3
AC494	17	19	2	534.8	615.4	137.7	487.6	72.7	17.1	46.2	5.5	21.9	3.4	8.2	1.1	5.7	0.8	109.3
AC494	19	21	2	407	353.8	100.3	374.4	58.4	13.9	38.3	4.5	17.9	2.9	7.1	0.9	5.6	0.8	93.7
AC497	19	21	2	396.4	130.2	92.4	386.1	69.1	17.4	67.1	8.8	41.6	8.2	21.7	3	17	2.5	302.2
AC509	26	28	2	278	294.8	82.9	282.3	52.4	13.3	37.3	5.3	25.3	4.3	10.2	1.4	8.3	1.2	102.6
AC511	20	22	2	241.6	810.7	68.4	246.1	47.5	11	41.3	6.2	31.5	5.9	14.4	2.4	13.2	1.9	152.4
AC511	22	24	2	171.2	378.3	50.5	207.6	45.3	12.3	52	8	46.1	8.9	23.1	3.7	20.4	2.9	267.9
AC518	21	23	2	462.1	800.9	77.3	221.6	23.1	3.5	11.6	1.6	5.9	0.9	1.7	0.2	1.3	0.1	18.5
AC520	31	33	2	514.9	1044.1	161.9	664.8	128.7	32.5	131.4	18.6	105	18.9	48.3	6.2	36.6	4.8	532.1

	From	To	Interval	La2O3	CeO2	Pr6O11	Nd2O3	Sm2O3	Eu2O3	Gd2O3	Tb4O7	Dy2O3	Ho2O3	Er2O3	Tm2O3	Yb2O3	Lu2O3	Y2O3
Hole ID	(m)	(m)	(m)	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm
AC532	36	38	2	415.2	324.3	114.7	415.2	67.6	17.4	48.9	5.6	25.8	4.7	11.6	1.6	9.2	1.3	148.6
AC532	38	40	2	438.6	141.3	92.9	369.7	57.3	15.4	52	6	27.7	5.9	14.5	2	10.6	1.6	289.5
AC540	25	27	2	207.6	616.7	86	403.6	92.9	24.8	88.4	13.8	68.5	13.1	32.5	4.4	26.9	3.5	388.6
AC540	27	29	2	173.6	490.1	65	258.9	53.5	11.8	44.4	6.1	32.8	5.9	16.5	2.2	14.1	1.9	181.6
AC544	31	33	2	272.1	565.1	63.7	214.6	40.4	8.8	31.2	4.3	21.6	3.8	9.5	1.3	8.1	1.1	105.8
AC544	33	35	2	319	620.3	72.3	230.9	40.7	7.9	29.9	4.1	19.5	3.4	8.1	1.1	6.7	0.9	89.3
AC544	35	37	2	141.9	374.7	52	200.6	37.5	7.6	30.8	4.4	22.5	4.2	11.3	1.6	9.8	1.4	130.8

2012 JORC Code – Table 1

Section 1: Sampling Techniques and Data

Criteria	JORC Code Explanation	Commentary
Sampling techniques	Nature and quality of sampling (e.g., cut channels, random chips, or specific specialized industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc.). These examples should not be taken as limiting the broad meaning of sampling.	A total of 547 vertical aircore holes have been drilled by HRE on the Subron project. Maximum hole depth is 58 metres. All holes have been tested for supergene rare earth element (REE) mineralisation hosted within saprolitic clays and saprock basement. Drilling in 2021 overlapped extensively with areas previously aircore drilled by two companies exploring for gold (AngloGold Ashanti Ltd and Great Southern Gold Pty Ltd). One-metre samples were collected from the drill rig cyclone into plastic bags. All holes drilled in 2022 have been 2 metre composite sampled with respective 1 metre samples at end of hole. Overlying transported sediments are not routinely sampled as they do not contain anomalous amounts of REEs.
	Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.	For aircore drilling, regular air and manual cleaning of cyclone was conducted to minimise contamination. Certified standards and duplicate samples were submitted with drill sample submissions.
	Aspects of the determination of mineralisation that are Material to the Public Report.	Aircore drilling is used to obtain 1m samples which are collected in plastic bags. Samples ranging from 1m to 2m composites are taken for analysis. Sample size is 2-3 kilograms in weight. At LabWest Minerals Analysis (LabWest) in Perth, Western Australia, samples are dried, crushed, split and pulverized with a 0.1-gram sub-sample set aside for assay.
Drilling techniques	Drill type (e.g., core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc.) and details (e.g., core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc.).	The drill type is aircore, a form of reverse circulation (RC) drilling using slim rods and a 3.5-inch blade bit. The samples recovered are typically rock chips, clays and powder, similar to RC drilling.
Drill sample recovery	Method of recording and assessing core and chip sample recoveries and results assessed.	Aircore recovery is visually assessed by comparing drill chip volumes in sample bags for individual metres. Estimates of sample recovery are recorded on drill logs. Routine checks for correct sample depths are undertaken. Aircore sample recoveries are visually checked for recovery, moisture and contamination and are considered to be acceptable within industry standards.

Criteria	JORC Code Explanation	Commentary
	Measures taken to maximize sample recovery and ensure representative nature of the samples.	Due to the generally good drilling conditions through dry saprolite the site geologist observed the samples to be reasonably representative. Poor sample recovery was regularly recorded in the first couple of metres of a hole and often when near-basement saprock was intersected – usually less than a full metre is recovered. Wet samples with moderate recoveries are encountered most often in the transported sand/silcrete layer lying immediately above saprolite.
	Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.	No sample bias has been identified to date. Analysis and initial testwork indicate Rare earths to be preferentially present in the fine size fraction.
Logging	Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.	Chip/clay samples are geologically logged in enough detail to discern regolith and lithological units. Logging is appropriate for this style of drilling and current stage of the project.
	Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc.) photography.	Logging is qualitative in nature.
	The total length and percentage of the relevant intersections logged.	All aircore holes are geologically logged to their entirety.
Sub-sampling techniques and sample preparation	If core, whether cut or sawn and whether quarter, half or all core taken.	Not applicable.
	If non-core, whether riffled, tube sampled, rotary split, etc. and whether sampled wet or dry.	One-metre samples are collected from a cyclone into plastic bags. Two-metre composites and single metre samples are collected by spearing each plastic bag with a scoop down the side of the bag and dragging it back up the side of the bag so as not to lose any sample – this achieves a representative sample from top to bottom through the entire bag. The vast majority of samples are dry sampled.
	For all sample types, the nature, quality and appropriateness of the sample preparation technique.	Sampling technique is appropriate for the sample types and stage of the project.
	Quality control procedures adopted for all sub-sampling stages to maximize representivity of samples.	QAQC procedures involve the use of certified standards every 20 th sample.
	Measures taken to ensure that the sampling is representative of the in-situ material collected, including for instance results for field duplicate/second-half sampling.	A field duplicate is taken every 20 th sample.
	Whether sample sizes are appropriate to the grain size of the material being sampled.	The sample size of 2-3 kilograms is considered appropriate to the grain size and style of mineralisation being investigated.

Criteria	JORC Code Explanation	Commentary
Quality of assay data and laboratory tests	The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.	Analyses are done at LabWest using their AF-02S technique: lithium meta/tetraborate fusion with ICP-MS/OES finish. This technique is considered to be a 'total' digest. A suite of 15 REEs – lanthanum (La), cerium (Ce), praseodymium (Pr), neodymium (Nd), samarium (Sm), europium (Eu), gadolinium (Gd), terbium (Tb), dysprosium (Dy), holmium (Ho), erbium (Er), thulium (Tm), ytterbium (Yb), lutetium (Lu), and yttrium (Y) – plus scandium (Sc), thorium (Th) and uranium (U), and oxides of aluminium (Al), calcium (Ca), iron (Fe), magnesium (Mg) and phosphorus (P), are measured.
	For geophysical tools, spectrometers, handheld XRF instruments, etc., the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.	Not applicable.
	Nature of quality control procedures adopted (e.g., standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e., lack of bias) and precision have been established.	OREAS standards and/or blanks are inserted every 20 th sample. Field duplicates are taken every 20 th sample. LabWest uses OREAS standards, blanks and sample repeats. Acceptable levels of accuracy have been achieved.
Verification of sampling and assaying	The verification of significant intersections by either independent or alternative company personnel.	Significant intersections have yet to be verified by an independent geological consultant. They have been verified by alternative company geological personnel.
	The use of twinned holes.	No twinned holes have been drilled to date. Some drilling may have been twinned due to failed initial drill hole. Twinned holes are planned for future resource extension and metallurgical drilling required.
	Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.	All data have been entered into Excel spreadsheets; merged assays and validated.
	Discuss any adjustment to assay data.	Assay data has been adjusted from elemental lanthanides to oxides.
Location of data points	Accuracy and quality of surveys used to locate drillholes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.	Hole collars are surveyed using a hand-held Garmin Etrex 22x GPS with ±3 metre accuracy. Northings, eastings and elevations are recorded using the hand-held GPS.
	Specification of the grid system used.	GDA94 z51.

Criteria	JORC Code Explanation	Commentary
	Quality and adequacy of topographic control.	The Subron project is located in relatively flat terrain. Topographic control is provided by Landgate's Digital Elevation Model over the region which has an expected horizontal accuracy of 10 metres and vertical accuracy of 2 metres (both 95% confidence interval).
Data spacing and distribution	Data spacing for reporting of Exploration Results.	Generally 400 metres x 200 metres.
	Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.	Data spacing is considered sufficient for this style of mineralisation to establish Inferred Mineral Resources. The mineralisation occurs as extensive, generally flat lying supergene blankets hosted in saprolitic clays.
	Whether sample compositing has been applied.	All holes have been assayed by 2 metre composite samples, compiled from 1 metre drilled samples. Additionally, a 1 metre end-of-hole sample is submitted for a 62 multi-element assay. Sample jobs were submitted inclusive of standards, blanks and field duplicates.
Orientation of data in relation to geological structure	Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.	Sampling is likely to be unbiased as vertical holes are intersecting flat lying mineralisation.
	If the relationship between the drilling orientation and the orientation of key mineralized structures is considered to have introduced a sampling bias, this should be assessed and reported if material.	Drilling orientation is unlikely to be biased; however closer-spaced drilling may be drilled in NE-SW drill line orientation, still with vertical dip.
Sample security	The measures taken to ensure sample security.	Sample Security protocols ensured experienced field assistants to deliver samples to a freight company in Esperance, which provided a direct delivery service to LabWest in Perth.
Audits or reviews	The results of any audits or reviews of sampling techniques and data.	No audits or reviews have been commissioned to date.

Section 2: Reporting of Exploration Results

Criteria	JORC Code Explanation	Commentary
Mineral tenement and land tenure status	Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.	Exploration licence E63/1972 is located 55 kilometres east-north-east of Salmon Gums in Western Australia. It consists of 80 graticular blocks comprising an area of 224 km ² . It is situated on unallocated crown land. The registered holder of the tenement is Heavy Rare Earths Limited (HRE). Full native title rights have been granted over the tenement and surrounding lands to the Ngadjju people, with whom cultural heritage surveys are undertaken in advance of substantial disturbance exploration works.
	The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.	The tenement is in good standing. There are no impediments to operating on the tenement other than requirements of the DMPE and the Heritage Protection Agreement, all of which are industry standard.
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	AngloGold Ashanti and Great Southern Gold previously worked in the area of E63/1972 exploring for gold mineralisation. Surface geochemical sampling and aircore drilling was undertaken by both companies but no significant gold mineralisation was discovered. Both companies assayed bottom of hole samples for a suite of multi-elements including REEs. Anomalous bedrock REE values were recorded in numerous holes from their drilling. Great Southern Gold also assayed for La and Ce for the entire length of a number of holes. AngloGold Ashanti flew an airborne magnetic/radiometric survey to assist with mapping of buried bedrock lithologies. Buxton Resources and Toro Energy also previously worked in the area of E63/1972 exploring for gold and nickel mineralisation, and uranium mineralisation, respectively. Both companies flew time-domain electromagnetic surveys to aid in their exploration targeting. No significant mineralisation was discovered.
Geology	Deposit type, geological setting and style of mineralisation.	The deposit type being investigated is residual clay-hosted supergene rare earth mineralisation. This style of supergene rare earth mineralisation is developed over bedrock granitic rock types (granites and granitic gneisses) or intrusions which contain anomalous levels of REEs. Although at times low grade, associated low mining and processing costs can make this type of deposit profitable to exploit.

Criteria	JORC Code Explanation	Commentary
Drillhole Information	A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drillholes: - easting and northing of the drillhole collar - elevation or RL (Reduced Level – elevation above sea level in metres) of the drillhole collar - dip and azimuth of the hole - down hole length and interception depth - hole length.	All relevant data for the significant drilling is included in drill collar table provided.
Data aggregation methods	In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g., cutting of high grades) and cut-off grades are usually Material and should be stated.	All REE assay results have been converted to oxide (REO) values using the following industry standard element-to-stoichiometric oxide conversion factors: $\text{La}_2\text{O}_3 = \text{La} \times 1.1728$ $\text{CeO}_2 = \text{Ce} \times 1.2284$ $\text{Pr}_6\text{O}_{11} = \text{Pr} \times 1.2082$ $\text{Nd}_2\text{O}_3 = \text{Nd} \times 1.1664$ $\text{Sm}_2\text{O}_3 = \text{Sm} \times 1.1596$ $\text{Eu}_2\text{O}_3 = \text{Eu} \times 1.1579$ $\text{Gd}_2\text{O}_3 = \text{Gd} \times 1.1526$ $\text{Tb}_4\text{O}_7 = \text{Tb} \times 1.1762$ $\text{Dy}_2\text{O}_3 = \text{Dy} \times 1.1477$ $\text{Ho}_2\text{O}_3 = \text{Ho} \times 1.1455$ $\text{Er}_2\text{O}_3 = \text{Er} \times 1.1435$ $\text{Tm}_2\text{O}_3 = \text{Tm} \times 1.1421$ $\text{Yb}_2\text{O}_3 = \text{Yb} \times 1.1387$ $\text{Lu}_2\text{O}_3 = \text{Lu} \times 1.1371$ $\text{Y}_2\text{O}_3 = \text{Y} \times 1.2699$ These oxide values are summed to produce a TREO grade for each assay sample. Two minimum grade cut-off are used; 1000ppm TREO & 300 ppm HREO. No internal dilution is included in intercept intervals presented. No high cut-off has been applied. Length weighted averages have been applied to intersections.
	Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low-grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.	Intervals reporting >1000 ppm TREO & >300ppm HREO are reported separately.

Criteria	JORC Code Explanation	Commentary
	The assumptions used for any reporting of metal equivalent values should be clearly stated.	No metal equivalent values have been used.
Relationship between mineralisation widths and intercept lengths	If the geometry of the mineralisation with respect to the drillhole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (e.g., 'down hole length, true width not known').	To date the targeted mineralisation appears to occur in flat lying sheets and drill holes have all been drilled at 90° vertically. The down hole length of intercept is effectively a true thickness of mineralisation. Interpretation of NW-SE orientation structural control on mineralisation is being reviewed.
Diagrams	Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drillhole collar locations and appropriate sectional views.	All significant intercepts and respective drill sections have been previously reported. Distribution of rare earths when a >300ppm HREO cut-off is applied, are presented in a pie graph image to visualize the % occurrence of each lanthanide.
Balanced reporting	Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.	Summary averages of all significant intercept assays for all mineralised intervals > 1000 TREO & >300 ppm HREO respectively are presented in summary statements. This was investigated and calculated to understand the HREO distribution within mineralised Subron system.
Other substantive exploration data	Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	Particle size analysis on mineralised saprolite shows that, on average: - 78.5% of REEs are confined to the -25 µm size fraction - the -25 µm fraction comprises 37.2% of the bulk saprolite feed mass - the REE grade of the -25 µm fraction is 116% higher than the bulk saprolite feed grade. Preliminary leach testwork has shown up to 91% TREO recovery from Subron South using 5% hydrochloric acid at 30°C. U and Th values have been previously reported as they are considered to be deleterious elements in rare earth processing. The highest values recorded for these elements on the project to date are 52 ppm U₃O₈ and 81 ppm ThO₂.
Further work	The nature and scale of planned further work (e.g., tests for lateral extensions or depth extensions or large-scale step-out drilling).	Comprehensive metallurgical and mineralogical characterisation testwork is planned to identify and understand REE-bearing mineral species.
	Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.	HRE deems this to be commercially sensitive.