



Shallow High-Grade Gold-Silver Results Extend Evergreen Discovery Zone

AGC is building a significant precious and base metals business across its 2,600km² landholding in the South Cobar Basin, NSW. Its Achilles discovery (2024) hosts an initial 38.5Moz AgEq Resource (58% Indicated), with ongoing drilling delivering strong results and a second resource opportunity emerging only 30km away at Browns-Evergreen (acquired 2025).

The recent acquisition of the Junee gold project 230km south of AGC's South Cobar projects adds a pure gold project to the portfolio.

AGC is well positioned to grow into a major resource development company. See ASX:AGC for more information and www.austgoldcopper.com.au

Capital Structure

Shares: 332m
Options: 7.5m
Perf Rights: 11.5m
Cash: A\$7m (31 Jul 26)
Debt: Nil

Australian Gold and Copper Ltd (ASX: AGC) ("AGC" or the "Company") is pleased to report initial assay results from reverse circulation ("RC") drilling completed at the recently announced Western Discovery Zone (Hillston Structure) at the Evergreen Prospect, part of the Company's South Cobar Project in NSW.

The Company completed 21 RC holes for 2,593m targeting extensions to the shallow high-grade mineralisation reported from diamond holes 26DDBR013 and 26DDBR017. The RC program tested mineralisation up-dip and along strike from 26DDBR017, with holes drilled to depths of up to 160m.

Initial assay results have been received for five RC holes, with significant shallow gold, silver and base-metal mineralisation returned.

The results continue to define a broad, coherent and gold-rich polymetallic mineralised system across northern Evergreen, with substantial widths of gold-zinc mineralisation accompanied by silver, copper and lead.

Significant new results include:

- EGRC005: **15m at 4.8g/t Au from 61m to end of hole with mineralisation open at depth, incl. 2m at 10.2g/t Au from 70m**
- EGRC008: drilled more than 100m to the south of EGRC005 and returned **13m at 3.3g/t Au, 264g/t Ag, 0.8% Cu, 4.8% Zn, 5.3% Pb from 99m** to end of hole with mineralisation open at depth
 - incl. **10m at 3.9g/t Au, 336g/t Ag, 0.9% Cu, 6.1% Zn, 6.6% Pb** from 100m
 - and incl. **3m at 5.3g/t Au, 852g/t Ag, 0.3% Cu, 8.1% Zn, 9.3% Pb** from 100m
 - incl. **copper interval 5m at 3.5g/t Au, 104g/t Ag, 1.6% Cu, 3.3% Zn, 5.4% Pb** from 105m
- EGRC006: drilled north of EGRC005 and returned 10m at 1.1g/t Au from 42m and 17m at 0.7g/t Au from 89m

Widths are downhole widths.

These results extend the recently reported high-grade gold-silver & base-metals mineralisation in 26DDBR017 (ASX AGC 2 Sept 2026), which returned:

- **17m at 5.3g/t Au, 163g/t Ag, 0.8% Cu and 17.3% Pb+Zn** from 128m
- Including **8m at 10.4g/t Au, 311g/t Ag, 1.2% Cu and 29.0% Pb+Zn** from 129m.

The strong gold grades over broad shallow RC intervals, together with high-grade silver and base metals in EGRC008 and 26DDBR017, provide an important precious and base-metal contribution to the broader Evergreen mineralised system.

AGC Exploration Manager, Gordon Barnes, commented:

"The Evergreen RC and diamond drilling program continues to deliver excellent results, with shallow high-grade gold, silver and base-metal mineralisation now intersected across multiple holes."

"Importantly, these initial RC assays strengthen our understanding of the continuity of the western discovery zone between diamond holes 26DDBR013 and 26DDBR017. EGRC005 and EGRC008 both ended in mineralisation, confirming the system remains open at depth in those positions."

"EGRC008 is particularly important because it demonstrates the high-tenor polymetallic character of the zone, with strong gold and silver accompanied by copper, zinc and lead. The remaining RC assays, together with the next phase of RC drilling scheduled to resume in November, will be important in defining the strike extent, width and continuity of this emerging high-grade zone."

AGC Managing Director, Glen Diemar, commented:

"These are outstanding shallow results from Evergreen and an important follow-up to the recent diamond drilling discovery. EGRC005 and EGRC008 confirm that high-grade mineralisation continues in shallow RC drilling, with EGRC008 returning a particularly strong gold-silver-base metal intercept."

"Evergreen is continuing to grow as a significant mineralised system. We are seeing gold, silver, zinc, lead and copper returned over meaningful widths at shallow depths, with mineralisation remaining open and 16 RC holes still pending assays."

"The speed of follow-up from diamond drilling to RC drilling has been excellent, and the results continue to support our strategy of advancing Evergreen towards an initial Mineral Resource Estimate."

"I look forward to presenting at the Australian Gold Conference in Sydney later this week."



Figure 1: EGR005 drill hole chip tray showing gold assays down hole **15m @ 4.8g/t Au** from 61m to end of hole.




Figure 2: Cross section through broad mineralisation in EGRC005 and 26DDBR013. Holes with blue traces have assays pending. (50m section).




Figure 3: Cross section through the mineralised section in EGRC008 and 26DDBR017. (50m section).




Figure 4: Oblique views looking down and to the north west at EGRC008 and 26DDBR017 with two holes pending assays 50m clipping (left) and 300m clipping showing results and holes with assays pending in blue traces (right).




Figure 5: Cross section through the broad mineralised section in EGR006. (50m section).




Figure 6: Plan map showing gold results at Evergreen with holes being reported with green collars, holes pending assays with blue collars.

Shallow High-Grade Mineralisation

The significant gold intercepts in RC holes EGRC005, EGRC006 and EGRC008 confirm continuity of shallow high-grade polymetallic mineralisation between diamond holes 26DDBR013 and 26DDBR017 at Evergreen.

This emerging zone has now been tested over approximately 210m of strike and remains open to the north, south and at depth. Significantly, EGRC005 and EGRC008 both ended in mineralisation, with further drilling required to test the depth extent of the zone.

High-Grade Gold-Silver-Base Metal Zone

The broader northern gold-zinc mineralised system is complemented by the recently discovered shallow high-grade gold-silver-base metal zone intersected in 26DDBR017.

As announced on 2 September 2026, 26DDBR017 returned:

17m at 5.3g/t Au, 163g/t Ag, 0.8% Cu and 17.3% Pb+Zn from 128m
including:

8m at 10.4g/t Au, 311g/t Ag, 1.2% Cu and 29.0% Pb+Zn from 129m

The new RC results support the continuity of this high-grade mineralised position and provide further evidence of a shallow, gold-rich polymetallic zone within the broader Evergreen mineralised corridor.

RC Drilling

A total of 21 RC holes for 2,593m were completed at Evergreen, targeting extensions to the high-grade mineralisation.

The RC program tested mineralisation up-dip and along strike from 26DDBR017, with holes drilled to depths of approximately 160m.

The completed RC drilling represents an important next step in determining the strike extent, width, orientation and continuity of the emerging high-grade zone.

Results from the program will also assist AGC in integrating the gold-silver-base metal mineralisation around 26DDBR017 with the broader gold-zinc-rich mineralised system being defined across northern and eastern Evergreen, (ASX AGC 23 September 2026).

Assays have been received for five RC holes, EGRC005 to EGRC009, with assays pending for the remaining 16 holes.

Two of the RC holes, EGRC005 and EGRC008, ended in mineralisation. Drilling in these holes was stopped due to broken ground and water ingress. A larger RC drilling rig with increased air capacity has been secured to continue the RC program at Evergreen, with drilling scheduled to resume in early November, subject to permitting.

Evergreen Continues to Grow in Scale

The combined diamond and RC drilling is rapidly advancing AGC's geological understanding of Evergreen.

Diamond drilling has defined a broad, vertically extensive gold-zinc-rich polymetallic mineralised system across northern Evergreen, with repeated substantial widths of mineralisation and higher-grade internal zones.

Within this broader mineralised system, 26DDBR017 identified an exceptional high-grade gold-silver-base metal zone that has now been supported by initial RC drilling.

Together, the results demonstrate the evolving scale and metal diversity of Evergreen and provide a strong platform for continued definition of the mineralised system.

What's Next

Further RC assay results are expected in October and early November. Further diamond assay results will also be reported as they become available from the ongoing assaying program focused on previously unsampled historic drill core and additional sampling of AGC's diamond core.

Additional drill site permitting is underway for Evergreen, with RC drilling expected to resume in November once approvals are received.

South Cobar Project

FY2027 Targets & Programs




Figure 7: South Cobar Project situated west of the town of Lake Cargelligo NSW

Table 1: Details for RC drill holes at Evergreen reported in this release (GDA94).

Hole ID	Type	Depth (m)	East	North	RL	Dip	Az	Assay Status
EGRC001	RC	100	436451	6314556	183.8	-60.0	70.0	Pending
EGRC002	RC	100	436455	6314488	182.2	-60.0	70.0	Pending
EGRC003	RC	100	436476	6314451	183.8	-60.0	70.0	Pending
EGRC004	RC	118	436548	6314247	188.7	-60.0	256.0	Pending
EGRC005	RC	76	436497	6314194	188.2	-60.0	70.0	Received
EGRC006	RC	118	436486	6314246	187.9	-60.0	70.0	Received
EGRC007	RC	100	436539	6314150	187.2	-60.0	76.0	Received
EGRC008	RC	112	436551	6314117	186.7	-60.0	75.0	Received
EGRC009	RC	136	436588	6314047	186.1	-60.0	73.0	Received
EGRC010	RC	148	436576	6314145	187.1	-60.0	73.0	Pending
EGRC011	RC	124	436585	6314096	186.5	-60.0	63.7	Pending
EGRC012	RC	118	436640	6314077	186.4	-60.0	50.7	Pending
EGRC013	RC	130	436537	6314179	187.7	-60.0	41.3	Pending
EGRC014	RC	112	436513	6314230	188.5	-60.0	62.6	Pending
EGRC015	RC	124	436476	6314206	188.1	-60.0	61.4	Pending
EGRC016	RC	136	436639	6314137	186.6	-50.0	250.4	Pending
EGRC017	RC	131	436595	6314182	187.6	-50.0	250.0	Pending
EGRC018	RC	148	436562	6314067	186.3	-60.0	71.5	Pending
EGRC019	RC	160	436549	6314097	186.6	-60.0	71.3	Pending
EGRC020	RC	160	436541	6314125	186.9	-60.0	69.5	Pending
EGRC021	RC	142	436521	6314178	187.8	-60.0	71.6	Pending

Table 2 Significant intersections for new Evergreen holes reported in this release. Intervals represent downhole widths; true widths are currently unknown. Minimum cut-off of 0.2g/t Au or 20g/t Ag or 0.2% Cu or 2.0% Pb+Zn with internal dilution up to 4m.

Hole ID	Interval (m)	Au (g/t)	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)	Zn+Pb (%)	From (m)	Comment
EGRC005	15	4.8	6	0.1	0.4	0.1	0.5	61	Oxide, ended in Mineralisation
and Incl	2	10.2	5	0.2	0.5	0.1	0.6	70	Oxide
EGRC006	3	0.3	1	0.0	0.1	0.0	0.1	32	Oxide
	1	0.4	1	0.0	0.1	0.0	0.1	37	Oxide
	10	1.1	5	0.1	2.3	0.3	2.6	42	Oxide
and Incl	5	1.6	5	0.1	2.3	0.2	2.5	44	Oxide
	1	0.2	3	0.0	0.2	0.1	0.3	54	Oxide
	1	0.1	27	0.0	0.0	0.0	0.1	85	Oxide
	17	0.7	12	0.0	0.3	0.1	0.4	89	Oxide
incl	4	1.6	13	0.0	0.5	0.0	0.5	96	Oxide
and Incl	1	3.2	14	0.0	0.5	0.0	0.6	98	Oxide
EGRC007	2	0.4	7	0.1	0.5	0.1	0.5	98	
EGRC008	13	3.3	264	0.8	5.3	4.8	10.1	99	Ended in Mineralisation
incl	10	3.9	336	0.9	6.6	6.1	12.7	100	
and Incl	3	5.3	852	0.3	9.3	8.1	17.4	100	
and incl copper interval	5	3.5	104	1.6	5.4	3.3	8.7	105	Copper Interval
EGRC009	2	0.1	14	0.5	0.2	0.0	0.2	102	
	2	0.1	13	0.3	0.2	0.0	0.2	107	
	1	0.1	8	0.3	0.1	0.0	0.1	112	
	1	0.1	14	0.3	0.1	0.0	0.1	117	

Achilles Mineral Resource Estimate

Table 3: Achilles Mineral Resource Estimate (AGC ASX 16 December 2025).

Location	Category	Cutoff	Mt	AgEq g/t	Ag g/t	Au g/t	Zn %	Pb %	Moz AgEq
Open pit	Indicated	40	4.7	141	52	0.48	1.0	0.83	21.5
Open pit	Inferred	40	3.2	72	31	0.26	0.4	0.26	7.3
Underground	Indicated	80	0.3	130	62	0.32	0.9	0.54	1.1
Underground	Inferred	80	2.2	124	74	0.31	0.4	0.29	8.8
Combined	All	40-80	10.3*	116	51	0.37	0.7	0.53	38.5

*Rounding

Table 4: Mineral Resource Estimate reported by open pit oxide, transition and sulfide and underground sulfide categories (AGC ASX 16 December 2025).

Location	Category	Cutoff	Mt	AgEq g/t	Ag g/t	Au g/t	Zn %	Pb %	Moz AgEq
Open pit	Oxide	40	0.8	81	24	0.49	0.1	0.3	2.0
Open pit	Transition	40	0.9	113	40	0.64	0.1	1.1	3.3
Open pit	Sulfide	40	6.2	118	47	0.34	0.9	0.6	23.5
Underground	Sulfide	80	2.4	125	73	0.31	0.5	0.3	9.8
Total	Total	40-80	10.3	116	51	0.37	0.7	0.5	38.5

The preceding statements of Mineral Resources conform to the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves (JORC Code) 2012 Edition. The information in this announcement that relates to the current Mineral Resources for Achilles has been extracted from the ASX release by AGC entitled "Amendment to Initial Mineral Resource Estimate for Achilles Containing 38.5Moz Silver-Equivalent" dated 16 December 2025, available at www.austgoldcopper.com.au and www.asx.com.au ("AGC MRE Announcement").

AGC confirms that it is not aware of any new information or data that materially affects the information included in the AGC MRE Announcement in relation to estimates of Mineral Resources and that all material assumptions and technical parameters underpinning the estimates continue to apply and have not materially changed. AGC confirms that the form and context in which the Competent Person's findings are presented have not been materially modified from the announcement. Due to rounding to appropriate significant figures minor discrepancies may occur. Achilles' reported silver equivalent (AgEq) is consistent with the AGC MRE Announcement and is based on the following assumptions: $\text{AgEq} = \text{Ag (g/t)} + 92.6 \times \text{Au (g/t)} + 21.8 \times \text{Pb (\%)} + 32.1 \times \text{Zn (\%)}$, where: silver price is US\$35/oz and recovery is 83%, gold price is US\$3300/oz and recovery is 90%, lead price is US\$1,950/t and recovery is 92% and zinc price is US\$2,800/t and recovery is 95%. Copper is not included in the AgEq calculation for Achilles as it was not recovered in the metallurgical testing. In the Company's opinion, the silver, gold, zinc, lead included in the metal equivalent calculations have a reasonable potential to be recovered and sold.

References relating to this release

AGC ASX 10 June 2025, New Acquisition to Give Belt-Scale Control of South Cobar

AGC ASX 5 August 2025, New Acquisition Further Expands AGC Footprint in South Cobar

AGC ASX 7 August 2025, Metallurgical Tests Highlight Robust Recoveries at Achilles

AGC ASX 16 December 2025, Initial MRE for Achilles Containing 38.5Moz AgEq – Amended

AGC ASX 19 January 2026, Exceptional Silver Gold Grades – Resource upside Potential

AGC ASX 27 January 2026, Deep hole yields excellent silver gold results

AGC ASX 29 April 2026, Step out drilling underway at Achilles

AGC ASX 19 May 2026, Semi-massive copper-bearing sulfide zone at Evergreen

AGC ASX 24 July 2026, Quarterly Activities and 5B Cash Flow Report

AGC ASX 28 August 2026, Evergreen drilling results confirm broad mineralisation

AGC ASX 1 September 2026, New Western Gold-Silver Zone discovered at Evergreen

AGC ASX 2 September 2026, High Grade Gold-Silver Base-Metals Discovered at Evergreen

AGC ASX 23 September 2026, Strong Zinc-Gold Mineralisation Defines Northern Evergreen

This announcement has been approved for release by the Board of AGC.

ENDS

For enquiries:

Glen Diemar

Managing Director

Australian Gold and Copper Ltd

+61 434 827 965

gdiemar@austgoldcopper.com.au

www.austgoldcopper.com.au

Forward-Looking Statements

This announcement contains “forward-looking statements.” All statements other than those of historical facts included in this announcement are forward-looking statements. Where the Company expresses or implies an expectation or belief as to future events or results, such expectation or belief is expressed in good faith and based upon information currently available to the company and believed to have a reasonable basis. Although the company believes the expectations expressed in such forward-looking statements are based on reasonable assumptions, such statements are not guarantees of future performance and no assurance can be given that these expectations will prove to be correct as actual results or developments may differ materially from those projected in the forward-looking statements. Forward-looking statements are subject to risks, uncertainties and other factors, which could cause actual results to differ materially from future results expressed, projected or implied by such forward-looking statements. Such risks include, but are not limited to, copper, gold, and other metals price volatility, currency fluctuations, increased production costs and variances in ore grade or recovery rates from those assumed in mining plans, as well as political and operational risks and governmental regulation and judicial outcomes. Readers are cautioned not to place undue reliance on forward-looking statements due to the inherent uncertainty thereof. The forward-looking statements contain in this press release are made as of the date of this press release and except as may otherwise be required pursuant to applicable laws, the Company does not undertake any obligation to release publicly any revisions to any “forward-looking statement”.

Competent Persons Statement

The information in this document that relates to Exploration Results, including the drill hole data that underpins the Mineral Resource Estimate is based on information compiled by Mr Glen Diemar who is a member of the Australian Institute of Geoscientists. Mr Diemar is a full-time employee of Australian Gold and Copper Limited, and is a shareholder, however Mr Diemar believes this shareholding does not create a conflict of interest, and Mr Diemar has sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the 2012 Edition of the “Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves”. Mr Diemar consents to the inclusion in this announcement of the matters based on his information in the form and context in which it appears.

The information in this report that relates to Mineral Resource Estimates is based on and fairly represents information and supporting documentation compiled by Mr Arnold van der Heyden who is a Director of H & S Consultants Pty Limited. Mr van der Heyden is a member and Chartered Professional (Geology) of the Australian Institute of Mining and Metallurgy and has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration, and to the activity being undertaken, to qualify as a Competent Person as defined in the 2012 edition of the ‘Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves’ (JORC code). Mr van der Heyden consents to the inclusion in this report of the matters based on the information in the form and context in which it appears.

Previously Reported Information

The Company confirms that it is not aware of any new information or data that materially affects the information included in the original market announcements. The Company confirms that the form and context in which the Competent Person’s findings are presented have not been materially modified from the original market announcement.

Appendix I – JORC Code, 2012 Edition – Table 1

Section 1 Sampling Techniques and Data: **South Cobar Project, Evergreen RC drilling**

Criteria	JORC Code explanation	Commentary
Sampling techniques	<i>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</i>	RC: drilling was undertaken by Strike Drilling. RC drilling is considered the correct method of sampling for early stage, near surface, exploration target testing. 1m samples were collected via reverse circulation (RC) drilling using a cyclone splitter. Samples were mostly dry however below about 50m water was intercepted and has the potential to affect sample quality.
	<i>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</i>	RC: Sampling and QAQC procedures were developed and carried out by AGC staff. Standards and duplicates were inserted every 50m. Drilling is perpendicular to the strike of mineralisation as much as possible to ensure a representative sampling.
	<i>Aspects of the determination of mineralisation that are Material to the Public Report.</i> <i>In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</i>	RC: The RC drill chips were geologically logged and magnetic susceptibility and pXRF readings were taken on site. Samples were collected in 1m intervals from which 1-3kg was pulverised to produce a 50g charge for fire assay AA-24/AA-26 and four acid ICP analysis, ME-MS61 by ALS Perth Laboratory. Assay standards, blanks and duplicates are analysed as part of the standard laboratory analytical procedures. Company standards are also introduced into the sampling stream at a nominal ratio of 1 standard for every 50 samples.
Drilling techniques	<i>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</i>	RC hammer drilling used a truck mounted T450 or a track mounted UDR1200. 3 ½ inch tube.
Drill sample recovery	<i>Method of recording and assessing core and chip sample recoveries and results assessed.</i>	RC: Recoveries were generally good however wet samples recorded poorer recoveries.
	<i>Measures taken to maximise sample recovery and ensure representative nature of the samples.</i>	RC: Sample sizes were monitored and the cyclone was regularly agitated to reduce the potential for sample contamination. Samples submitted to the lab for analysis were generally in the range 1.5kg to 3kg.
	<i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i>	The relationship between sample grade and recovery has been assessed. It is possible that drilling technical issues did lead to loss in some holes due to drilling difficulties and washing away the relatively soft sulphide mineralisation.

Criteria	JORC Code explanation	Commentary
Logging	<i>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</i>	RC: Systematic geological and geotechnical logging was undertaken. Data collected includes: • Nature and extent of lithologies and alteration. • Relationship between lithologies. • Amount and mode of occurrence of minerals such as pyrite and chalcopyrite.. • Magnetic susceptibility recorded at 1m intervals
	<i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</i>	RC: Logging was generally qualitative except for % sulphides. Photographs taken of chip trays and stored for future reference. Logs were later compared to pXRF readings.
	<i>The total length and percentage of the relevant intersections logged.</i>	The entire hole is all geologically logged (100%).
Sub-sampling techniques and sample preparation	<i>If core, whether cut or sawn and whether quarter, half or all core taken.</i>	Not applicable.
	<i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i>	RC samples were collected via a cyclone cone splitter on the rig.
	<i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i>	RC cyclone cone splitters are considered the most appropriate method. Mag sus and pXRF was recorded on site directly into the calico sample bag as this was the most homogenous sample. The calico bag 1.5-3kg was sent to lab for pulverizing and analysis which is the most appropriate method.
	<i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i>	RC: Duplicates and certified standard reference materials by OREAS were sampled approximately every 50m. ALS also conduct internal checks every 20m.
	<i>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</i>	RC: Duplicates were sampled approximately every 50m and this is considered appropriate for greenfields drilling. pXRF also used as a first pass test and these results are compared with lab results.
	<i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i>	The samples sizes average approximately 2kg per metre and are considered appropriate for the fine grain nature of the volcanic and sedimentary material being sampled.
Quality of assay data and laboratory tests	<i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i>	The results reported in this announcement are based on laboratory assay results. The samples were sent for four acid digest which is considered a near total digest for most minerals. Inductively coupled plasma (ICP) produces ultra low detection analysis and is considered the most appropriate method for exploration sampling. 4-acid digest ICP analysis was completed by ALS. This method is considered nearly total digest at the detection limits and for the elements reported (ALS method: ME-MS61, 48 element four-acid digest). Gold primarily by photon assay (Au-PA01) and then by 50g fire assay (Au – AA24) if needed.
	<i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make</i>	Magnetic susceptibility was recorded for each metre by a Terraplug KT-10 magnetic susceptibility metre.

Criteria	JORC Code explanation	Commentary
	<i>and model, reading times, calibrations factors applied and their derivation, etc.</i>	
	<i>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</i>	Appropriate standards and duplicates were inserted into the sample stream. Magnetic susceptibility readings were taken in isolation away from any other material. Acceptable levels of accuracy for the magsus readings were established and readings were consistent or repeated if not.
Verification of sampling and assaying	<i>The verification of significant intersections by either independent or alternative company personnel.</i>	Assays are checked against logging and core photos. Significant intersections are calculated by numerous company personnel as a secondary check and compiled by the competent person.
	<i>The use of twinned holes.</i>	Twinned holes were not completed in this program.
	<i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i>	Data was recorded onto a handheld device and downloaded into a field laptop. Logging and weights data was completed directly into a field computer on the rig. Visual validation as well as numerical validation was completed by two or more geologists. MX Deposit is our database software which has validation steps.
	<i>Discuss any adjustment to assay data.</i>	No adjustments made to the data.
Location of data points	<i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i>	Initially, a handheld Garmin GPSmap was used to pick up collars with an averaged waypoint accuracy of 1m. Then collar locations are surveyed by a registered surveyor on a DGPS, which has an accuracy of 10mm. Down hole surveys were collected every 6m on completion of hole using a north-seeking gyro.
	<i>Specification of the grid system used.</i>	Coordinates picked up using WGS84 and transformed into Map Grid of Australia 1994 Zone 55.
	<i>Quality and adequacy of topographic control.</i>	Using government data topography and 2017 DTM data
Data spacing and distribution	<i>Data spacing for reporting of Exploration Results.</i>	Drill holes were preferentially located to most prospective areas to test along strike and down dip. Typically, 80m or 40m step outs are preferred.
	<i>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i>	RC drilling was a second pass drill program with variable spacing to best test the targets. Step outs were between 50m to 200m and in a dice five pattern to enhance drill coverage and best start modelling geology and grade.
	<i>Whether sample compositing has been applied.</i>	No compositing applied.

Criteria	JORC Code explanation	Commentary
<i>Orientation of data in relation to geological structure</i>	<i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i>	The orientation of sampling was designed perpendicular to strike and dip as much as possible to achieve relatively unbiased sampling.
	<i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i>	The true width of mineralisation has not been estimated yet. True width will be further assessed on analysis of orientated structural data. Further drilling is required to confirm the geometry and true thickness of mineralisation.
<i>Sample security</i>	<i>The measures taken to ensure sample security.</i>	Samples are transported by company personnel to secure storage area in Lake Cargelligo and placed in cages for transportation to the lab. Freight companies transport the cages directly to the lab in Adelaide or Orange.
<i>Audits or reviews</i>	<i>The results of any audits or reviews of sampling techniques and data.</i>	A resource geologist from H&S consultants has been to site and audited or reviewed our procedures. This site visit occurred in October 2025.

Section 2 Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
<i>Mineral tenement and land tenure status</i>	<i>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i> <i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i>	EL6321 Browns Reef licence is located 4km west of Lake Cargelligo NSW. The tenement is held by South Cobar Resources PL, a subsidiary of Australian Gold and Copper Ltd. Ground activity and security of tenure are governed by the NSW State government via the Mining Act 1992. Land access was granted.
<i>Exploration done by other parties</i>	<i>Acknowledgment and appraisal of exploration by other parties.</i>	The Browns Reef base metal mineralisation was discovered by the landowner who recognised outcropping gossanous material. The prospect was subsequently systematically developed by Jennings Industries-Electrolytic Zinc Company of Australia (EZ)-Esso Joint Venture, and later by Comet Resources. The most recent exploration was carried out by Kidman Resources which was acquired by Wesfarmers in 2019 and who sold the project to Eastern Metals in 2021.
<i>Geology</i>	<i>Deposit type, geological setting and style of mineralisation.</i>	Structurally controlled, polymetallic Cu, Pb, Zn, Ag, Au deposit extending along the Woorara Fault, and the Preston Formation and Clements Formation geological unconformity.
<i>Drill hole Information</i>	<i>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</i> <i>easting and northing of the drill hole collar</i> <i>elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</i>	See all material drill hole information in the table 1 of this report.

Criteria	JORC Code explanation	Commentary
	- dip and azimuth of the hole - down hole length and interception depth - hole length.	
	<i>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</i>	All info was included. Reported intercepts are down hole widths.
Data aggregation methods	<i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.</i>	When reported, intercepts are down hole widths. Once assays are returned, minimum cut off will be 0.2g/t Au or 20g/t Ag or 2.0% Pb+Zn or 0.2% Cu with internal dilution up to 4m. The higher-grade intercepts are reported with higher cut off grades only to demonstrate the effect of the high-grade zones across the lower grade intervals.
	<i>Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i>	When reported, high-grade intervals are only reported where they differ significantly to the overall interval. Reporting of the shorter intercepts allows a more thorough understanding of the overall grade distribution.
	<i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i>	AgEq used for reporting at Achilles drilling and MRE only – Silver equivalent was calculated using recoveries of 83% for Ag, 90% for Au, 95% for Zn and 92% for Pb based on recent test work conducted by the Company. Drill hole sulfide equivalent silver formula Reporting 12 month average metal prices to August 2025 used were US\$31.6/oz for Ag, US\$2,700/oz for Au, US\$2,850/t for Zn, US\$2,000/t for Pb. The applied formula was: $AgEq(g/t) = Ag(g/t) + 92.6 * Au(g/t) + 32.1 * Zn(\%) + 21.8 * Pb(\%)$. MRE sulfide equivalent silver formula Reporting 12 month average metal prices to November 2025 used in the MRE were US\$35/oz for Ag, US\$3,300/oz for Au, US\$2,800/t for Zn, US\$1,950/t for Pb. MRE sulfide equivalent silver formula is: $AgEq = Ag + Pb \times 21.8 + Zn \times 32.1 + Au \times 92.6$ While the MRE oxide equivalent silver formula is: $AgEq = Ag + Au \times 104.6$ In the Company's opinion all elements included in the silver equivalency calculations have reasonable potential to be recovered and sold. Refer AGC ASX 7 August 2025 Metallurgical Tests Highlight Robust Recoveries at Achilles. For the silver equivalent formula applied to previously reported drill results, refer to ASX AGC 7 August 2025. Copper is not included in the AgEq calculation as it was not recovered in the metallurgy testing.
Relationship between	<i>These relationships are particularly important in the reporting of Exploration Results.</i>	The Browns Reef prospect has numerous semi-continuous steeply dipping mineralised zones.

Criteria	JORC Code explanation	Commentary
<i>mineralisation widths and intercept lengths</i>	<i>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</i>	Drilling is designed to intersect mineralisation as close to perpendicular as possible. Drill hole deviation will influence true width estimates of mineralisation.
	<i>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known').</i>	The true width of mineralisation has not been estimated yet. True width will be further assessed on analysis of orientated structural data.
<i>Diagrams</i>	<i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</i>	See figures in body of report
<i>Balanced reporting</i>	<i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i>	See body of report and previous releases on Evergreen
<i>Other substantive exploration data</i>	<i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i>	The geological results are discussed in the body of the report.
<i>Further work</i>	<i>The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).</i>	The Company is working towards an initial Mineral Resource Estimate at the Browns–Evergreen precious and base metal deposit, with 7,000m of resource definition drilling underway.
	<i>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i>	See figures and text in body of report.